



WEIGHT oz ( g)

CABLES : -

CHARACTERISTICS

NOMINAL IMPEDANCE	50 $\Omega$
FREQUENCY RANGE	0-3 GHz
TEMPERATURE RATING	-55/+155 °C
VSWR	AD Max
RF INSERTION LOSS	AD $\sqrt{F}$ dB Maxi
VOLTAGE RATING	500 Vrms Maxi
DIELECTRIC WITHSTANDING VOLTAGE	1500 Vrms mini
INSULATION RESISTANCE	5000 Ma mini
HERMETIC SEAL	NA cc/s Atm.cm3/s
LEAKAGE (pressurized only)	NA psi MPa

STANDARDISATION

CABLE RETENTION

NA Lb mini  
N

CENTER CONTACT RETENTION

Axial force - mating end 6.075 Lb mini  
27 N

Axial force - opposite end 6.075 Lb mini  
27 N

Torque (Min) NA Inch.oz  
cm.N

RECOMMENDED TORQUES

Mating	NA	Inch.Lb cm.N
Panel nut	NA	Inch.Lb cm.N
Clamp nut	NA	Inch.Lb cm.N

CONSTRUCTION

CONNECTOR PARTS	MATERIALS	FINISH
BODY	BRASS	NICKEL
OUTER CONTACT	-	-
CENTER CONTACT	BERYLLIUM COPPER	GOLD
Insulators	PTFE	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
.	.	.	.	.
.	.	.	.	.
.	.	.	.	.
.	.	.	.	.

Initiated on 21-JUN-91

The information given here is subject to change without notice. Design changes may be in order to improve the product.



Superseded on