



Main

Product or component type	Communication card
Range compatibility	Altivar 61 Altivar 71 Altivar 61Q Altivar 71Q
Communication port protocol	DeviceNet
Connector type	1 screw connector 5 contacts at intervals of 5.08
Transmission rate	125 kbps 250 kbps 500 kbps

Complementary

Number of addresses	1...63
Exchange mode	Inputs : polled, change of state, cyclic Outputs : polled
Communication service	Allen-Bradley drive profile CiA 402 profile : "Device profile Drives and Motion Control" CIP AC Drive (02) profile Communication monitoring can be inhibited, adjustable I/O profile
Display type	1 dual colour LED MNS (status) Graphic display terminal control word received Graphic display terminal reference received
Product weight	0.66 lb(US) (0.3 kg)

Environment

Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.	Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------