












REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2012/10/22	Ruru	HB20-04PMFS-SS8001 To HB20-04PMFS-SW8001
B	LEN14A0096	2014/09/13	Feng_Li	Change Logo Direction
C	LE31650208	2016/05/03	Vicky	Update Note



△ Note:

- * ⌀ Important Dimension.
- * Waterproof Rate: IP68.
IP68: 1M depth of water in 24 Hrs.
(防水等級: IP68)
IP68: 水深一米測試 24 小時
- * Shell: Zinc Alloy ,Electrodeposition Coating ,Black.
- * Insulation: Nylon ,Black.
- * Female Pin: Copper Alloy ,Gold Plated.
- * Gasket: Silicone ,Gray.
- * Screw: Stainless Steel.
- * Recommended Panel Thickness 9mm(Max).

UNIT:mm



TITLE

PANEL SCREW 4PIN M CONN F PIN

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

SCALE
1:1

SIZE
A4

SHEET
1 OF 1

REV.
C

WC-REV.
A.3

QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO

HB20-04PMFS-SW8001

DRAWN BY

Vicky

DATE

2016-05-03

DWG NO

HB20-04PMFS-SW8001

CHECKED BY

Rita

DATE

2016-05-03

CUSTOMER

ALTW

APPROVED BY

Lisa

DATE

2016-05-03