9001KM1



Main

Range of product	Harmony 9001K Harmony 9001SK	
Product or component type	Light block	
Device short name	9001K	
Bulb base	BA 9s	
Light block supply	Direct via integral transformer (6 V)	

Complementary

Product weight	0.32 lb(US) (0.144 kg)
Light source	Incandescent
[Us] rated supply voltage	120 V AC

Environment

protective treatment	TC		
ambient air temperature for storage	-40158 °F (-4070 °C)		
ambient air temperature for operation	-13158 °F (-2570 °C)		
IP degree of protection	IP20 conforming to IEC 60529		
standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14		
product certifications	NEMA UL 508		
electrical shock protection class	Class II conforming to IEC 61140		
vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
shock resistance	50 gn conforming to IEC 60068-2-27		


Offer Sustainability

785901725237	785901725237
Compliant - since 0921 - Schneider Electric declaration of conformity	Compliant - since 0921 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Contractad warranty		
Warranty period	18 months	

Dimensions



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.