

+



NOTES:
1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS WITH THIS WIRING SYSTEM.

-
- A detailed diagram of a 16-pin D-sub connector. The connector is shown from a perspective view, highlighting its D-shaped profile. The pins are arranged in two rows of eight. The top row of pins is numbered 1 through 8, and the bottom row is numbered 9 through 16. The connector is shown with its protective shield, which has a D-shaped cutout on one side. The diagram is a black and white line drawing.




MAY 26 2006

~~ENGINEERING DEPT~~



PANDUIT™
CORP
TINLEY PARK, ILL 60477



ALL DIMENSIONS ARE GIVEN IN INCHES,
UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
[.X] ± [XXX] ± .0101.3
[.XX] ± .03(.8) ANGLES ±

DRAWN BY ISP

1	MATERIAL:	1
---	-----------	---

DATE	3-11-06
------	---------

PANEL: 20 GAGE C.R.S.
FACEPLATE: ABS

CHK'D	
-------	--

1.1. NUMBER	N/A
PRODUCT SPEC	N/A
WORK INSTRUCTION	N/A
SCALE	NONE
PART NO.	CPP48FMWBLY
DRAWING NO.	02479-075