

## Coaxial Cable Connector 25\_BMA-50-2-2/119\_N

### Description

Straight panel cable jack, flange mount

Interface standards

IEC 60169-33\_MIL-STD-348A/321



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	18 GHz

#### Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.0055 kg

#### Environmental Data

Operating temperature	-65 °C to 125 °C
2011/65/EC, RoHS	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Other body part	Stainless Steel	
Insulator	PFA / PTFE	

### Related Documents

Catalogue drawing	DCA-00008815
Assembly instruction	DOC-0000180997
Mounting hole	DOU-00008816

### Ordering Information

Single package	25_BMA-50-2-2/119_NE
Bulk 100 pcs package	25_BMA-50-2-2/119_NH

### Additional Information

Suitable cables	EZ_86_TP_M17
-----------------	--------------