

639948 Composite - CCTV Plus Audio or Power or Pan and Tilt CCTV Control Applications



For more Information
please call

1-800-Belden1



Description:

18 AWG bare copper conductor, foam fluorinated ethylene propylene insulation, bare copper braid shield, PVC jacket.

Usage (Overall)

Suitable Applications: CCTV plus Audio, Pan and Tilt CCTV Control

Coax

Physical Characteristics

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	18	Solid	BC - Bare Copper	0.040

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FFEP - Foam Fluorinated Ethylene Propylene	0.170

Inner Shield

Inner Shield Material:

Type	Inner Shield Material	% Coverage (%)
Braid	BC - Bare Copper	95

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

EU CE Mark: Yes

RG Type: 6/U

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Inductance:

Inductance (μH/ft)
0.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
16.100

Nominal Velocity of Propagation:

VP (%)
84.000

Nominal Delay:

Delay (ns/ft)
1.210

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

639948 Composite - CCTV Plus Audio or Power or Pan and Tilt CCTV Control Applications

6.400

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

2.200

Max. Operating Voltage - UL:

300 V RMS

Twisted Pair**Physical Characteristics****Conductor**

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
1	18	7	BC - Bare Copper	0.047

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PVC	0.062

Twisted Pair Color Code Chart:

Number	Color
1	Black and Red

Inner Shield

Inner Shield Material:

Inner Shield Material
Unshielded

Individual Shield**Electrical Characteristics**

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
24.000

Physical Characteristics (Overall)**Conductor****Outer Shield**

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter:

0.232 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

Non-UL Temperature Rating: 75°C

Bulk Cable Weight: 60.000 lbs/1000 ft.

Max. Recommended Pulling Tension: 129.000 lbs.

Min. Bend Radius/Minor Axis: 2.500 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:

CMP

639948 Composite - CCTV Plus Audio or Power or Pan and Tilt CCTV Control Applications

NEC Articles:	800
CEC/C(UL) Specification:	CMP
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	NFPA 262
C(UL) Flame Test:	FT6

Suitability

Suitability - Indoor:	Yes
------------------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	539945

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
639948 8771000	1,000 FT	59.000 LB	NATURAL		#18 FFEPSH +1 PR#18 FEPPVCSIAM
639948 877500	500 FT	31.000 LB	NATURAL		#18 FFEPSH +1 PR#18 FEPPVCSIAM

Revision Number: 1 Revision Date: 06-28-2012

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.