





CONNECTOR DESIGNATORS **A-F-H-L-S** ROTATABLE COUPLING





STYLE 2
(STRAIGHT
See Note 1)




* Length ± .060 (1.52)
Min. Order
Length 1.5 Inch
(See Note 6)




STYLE 2
(45° & 90°
See Note 1)



STYLE L
Light Duty (Table IV)



STYLE G
Light Duty (Table V)



See inside back cover fold-out or pages 13 and 14 for unabridged Tables I and II.

TABLE III: ELBOW DIMENSIONS

Shell Size		E		F		G		H	
Conn.	Desig.	Max		Max		Max		Max	
A-F-L-S	H								
08	09	.457	(11.6)	2.030	(51.6)	.500	(12.7)	2.040	(51.8)
10	11	.520	(13.2)	2.030	(51.6)	.595	(15.1)	2.040	(51.8)
12	13	.582	(14.8)	2.090	(53.1)	.610	(15.5)	2.160	(54.9)
14	15	.645	(16.4)	2.150	(54.6)	.700	(17.8)	2.180	(55.4)
16	17	.738	(18.7)	2.240	(56.9)	.885	(22.5)	2.250	(57.2)
18	19	.926	(23.5)	2.340	(59.4)	.975	(24.8)	2.340	(59.4)
20	21	.926	(23.5)	2.340	(59.4)	.975	(24.8)	2.340	(59.4)
22	23	1.020	(25.9)	2.540	(64.5)	1.125	(28.6)	2.510	(63.8)
24	25	1.020	(25.9)	2.540	(64.5)	1.125	(28.6)	2.510	(63.8)
28		1.145	(29.1)	2.680	(68.1)	1.225	(31.1)	2.620	(66.5)
32		1.207	(30.7)	2.680	(68.1)	1.575	(40.0)	2.620	(66.5)
36		1.238	(31.4)	2.680	(68.1)	1.775	(45.1)	2.620	(66.5)

TABLE IV: CABLE ENTRY

Dash No.	J		Cable Range			
	Max		Min		Max	
01	.781	(19.8)	.062	(1.6)	.125	(3.2)
02	.968	(24.6)	.125	(3.2)	.250	(6.4)
03	1.046	(26.6)	.250	(6.4)	.375	(9.5)
04	1.156	(29.4)	.250	(6.4)	.500	(12.7)
05	1.218	(30.9)	.375	(9.5)	.625	(15.9)
06	1.343	(34.1)	.500	(12.7)	.750	(19.1)
07	1.468	(37.3)	.625	(15.9)	.875	(22.2)
08	1.593	(40.5)	.625	(15.9)	1.000	(25.4)
09	1.718	(43.6)	.750	(19.1)	1.125	(28.6)
10	1.843	(46.8)	.875	(22.2)	1.250	(31.8)

TABLE V: CABLE ENTRY

Dash No.	K Max	Cable Range			
		Min		Max	
01	.593 (15.1)	.062 (1.6)	.125 (3.2)	.250 (6.4)	.375 (9.5)
02	.718 (18.2)	.125 (3.2)	.250 (6.4)	.500 (12.7)	.750 (19.1)
03	.873 (22.2)	.250 (6.4)	.500 (12.7)	.750 (19.1)	1.000 (25.4)
04	.968 (24.6)	.375 (9.5)	.750 (19.1)	1.125 (28.6)	1.250 (31.8)
05	1.109 (28.2)	.500 (12.7)	.750 (19.1)	1.250 (31.8)	1.500 (38.1)
06	1.218 (30.9)	.625 (15.9)	1.000 (25.4)	1.500 (38.1)	1.750 (44.5)
07	1.343 (34.1)	.750 (19.1)	1.125 (28.6)	1.750 (44.5)	2.000 (50.8)
08	1.468 (37.3)	.875 (22.2)	1.250 (31.8)	2.000 (50.8)	2.250 (57.2)
09	1.593 (40.5)	1.000 (25.4)	1.500 (38.1)	2.250 (57.2)	2.500 (63.5)
10	1.718 (43.6)	1.125 (28.6)	1.750 (44.5)	2.500 (63.5)	2.750 (69.9)

1. When maximum cable entry (page 21) is exceeded, Style 2 will be supplied.
Dimensions E, F, G and H will not apply. Please consult factory.
2. Metric dimensions (mm) are indicated in parentheses.
3. Cable range is defined as the accommodations range for the wire bundle or cable.
Dimensions shown are not intended for inspection criteria.
4. Interface O-Ring not supplied with connector designator A.

TABLE II: STANDARD FINISHES

GLENAIR	
SYMBOL	FINISH
B	Cadmium Plate, Olive Drab
C	Anodize, Black
G	Hard Coat, Anodic
M	Electroless Nickel
NF	Cadmium Plate, Olive Drab Over Electroless Nickel

**See Inside Back Cover
for Additional Finish Options**