Data Sheet

Within Series Adaptor 32_BNC-50-0-1/133_N

Description

Adaptor plug/plug BNC plug (male) / BNC plug (male)

Interface standard Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data Impedance 50 Ω Interface frequency max. 4 GHz VSWR DC - 4 GHz $\leq 1.06 + 0.04 \text{ f (GHz)}$ **Mechanical Data** Number of matings 500 Weight 0.0191 kg **Environmental Data** -65 °C to 165 °C Operating temperature 2011/65/EU (RoHS - including compliant

Material Data

Interface - BNC plug (male)

2015/863 and 2017/2102)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Interface - BNC plug (male)		
Interface - BNC plug (male) Piece Parts	Material	Surface Plating
	Material Brass	Surface Plating Gold Plating (Nickel underplated)
Piece Parts		-
Piece Parts Centre contact	Brass	Gold Plating (Nickel underplated)

Related Documents

Catalogue drawing

Coupling nut

DCA-00013766

Brass

Ordering Information

Single package

32_BNC-50-0-1/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

SUCOPLATE (R) Plating

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.



HUBER+SUHNER

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 32_BNC-50-0-1/133_NE