


JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
1680	6.0	4.10	32.0	402.2	300	C-6
1295	12.5	3.00	50.0	628.5	300	C-2R
93	12.8	1.04	15.0	188.6	700	C-6
1156	12.8	2.10	32.0	402.2	1,200	C-6
305	28.0	.51	15.0	188.6	300	*C-2V
1691	28.0	.61	15.0	188.6	1,000	2C-2R
2232	28.0	.643	17.0	213.7	2,000	CC-8
307	28.0	.67	21.0	264.0	300	*C-2V
2233	28.0	.77	21.0	264.0	2,000	CC-8
1683	28.0	1.02	32.0	402.2	500	2C-6

* SUPPORTED

		METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION TITLE S-8 SINGLE CONTACT BAYONET BASE LAMP					
B	DELETE PART NO'S 1073 & 1665	4/28/04	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.			
A	ADD PART NO. 2233	1/27/03	L. WENGSTROM	J.K.	4/28/04	A	55335	BAYONET SINGLE CONTACT S-8			
	RELEASED AS CAD	5/4/01	- CAD DRAWING -			SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	MANUAL REVISIONS NOT PERMITTED			NONE	5/4/01	4/28/04	B	1 OF 1	