


JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
1680	6.0	4.10	32.0	402.2	300	C-6
1295	12.5	3.00	50.0	628.5	300	C-2R
93	12.8	1.04	15.0	188.6	700	C-6
1156	12.8	2.10	32.0	402.2	1,200	C-6
305	28.0	.51	15.0	188.6	300	*C-2V
1691	28.0	.61	15.0	188.6	1,000	2C-2R
2232	28.0	.643	17.0	213.7	2,000	CC-8
307	28.0	.67	21.0	264.0	300	*C-2V
2233	28.0	.77	21.0	264.0	2,000	CC-8
1683	28.0	1.02	32.0	402.2	500	2C-6

\* SUPPORTED

		<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b> TITLE <b>S-8 SINGLE CONTACT BAYONET BASE LAMP</b>									
B DELETE PART NO'S 1073 & 1665 A ADD PART NO. 2233 RELEASED AS CAD		4/28/04 1/27/03 5/4/01		DRAWN BY L. WENGSTROM		APP'VD BY DATE J.K. 4/28/04		SIZE <b>A</b>		FSCM NO. <b>55335</b>		DRAWING NO. <b>BAYONET SINGLE CONTACT S-8</b>			
REV. NO. DESCRIPTION/ECO NUMBER		APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				SCALE <b>NONE</b>		RELEASED DATE <b>5/4/01</b>		REVISION DATE <b>4/28/04</b>		REV. NO. <b>B</b> SHEET 1 OF 1	