


D

C

B

A



- 1 HOUSING WILL ACCOMMODATE FLEXIBLE FLAT CABLE ON .100 CENTERS AND/OR #22-32 AWG WIRE WITH INSULATION RANGE OF .025 TO .056
- 2 HOUSING WILL INTERFACE WITH MOD II LOW PROFILE SHROUDED HEADERS AND AMPLATCH UNIVERSAL EJECTION STYLE PIN HEADER ASSEMBLIES WITH LATCH DIMENSIONS OF A=.576
- 3 BRIGHT TIN-LEAD PLATED CONTACTS ARE NOT RECOMMENDED FOR USE IN THIS HOUSING OVER 40 POSITIONS

OBSOLETE	1.660	3.450	3.334	3.380	3.100	31	64	1-487223-6
	1.560	3.250	3.134	3.180	2.900	29	60	1-487223-5
OBSOLETE	1.460	3.050	2.934	2.980	2.700	27	56	1-487223-4
OBSOLETE	1.410	2.950	2.834	2.880	2.600	26	54	1-487223-3
	1.310	2.750	2.634	2.680	2.400	24	50	1-487223-2
OBSOLETE	1.160	2.450	2.334	2.380	2.100	21	44	1-487223-1
	1.060	2.250	2.134	2.180	1.900	19	40	1-487223-0
	.910	1.950	1.834	1.880	1.600	16	34	487223-9
	.810	1.750	1.634	1.680	1.400	14	30	487223-8
	.710	1.550	1.434	1.480	1.200	12	26	487223-7
	.660	1.450	1.334	1.380	1.100	11	24	487223-6
	.560	1.250	1.134	1.180	.900	9	20	487223-5
OBSOLETE	.510	1.150	1.034	1.080	.800	8	18	487223-4
	.460	1.050	.934	.980	.700	7	16	487223-3
	.410	.950	.834	.880	.600	6	14	487223-2
	.310	.750	.634	.680	.400	4	10	487223-1
	F	E	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
H MOLL
8-4-88

CHK
G D MILLER
8-4-88

APVD
G D MILLER
8-4-88

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

TE Connectivity

HOUSING, RECEPTACLE, FFC
.100X.100 CENTERLINE, DOUBLE ROW

SIZE
A2

CAGE CODE
00779

DRAWING NO
C=487223

RESTRICTED TO

SCALE
4:1

SHEET
1 OF 1

REV
J1