



- 1 PIN:
0.00076[.000030] MINIMUM GOLD IN CONTACT AREA,
0.00381[.000150] MIN TIN ON SOLDER TAILS,
ALL OVER 0.00127[.000050] MINIMUM NICKEL
- 2 CUSTOMER TO PROVIDE CARD GUIDANCE SYSTEM
- 3 DATUMS AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER
- 4 CONNECTOR REQUIRES USE OF 2 - SIZE 2M SCREWS FOR FASTENING TO PRINTED CIRCUIT BOARD
- 5 ASSEMBLY KEYED FOR 5 VOLT CARDS
- 6 MATERIAL:
HOUSING & ORGANIZER: LCP; COLOR: BLACK
PIN: BRASS
HOLD-DOWN: PHOS BRZ
- 7 HOLD-DOWN: TIN

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

5	1,17,34	ALL	36,67	5146099-1
	35,51,68	OTHER PINS		
VOLTAGE KEYING & IDENTIFICATION	5.0	4.25	3.5	PART NUMBER
	[.197]	[.167]	[.138]	
"L" (PIN LENGTH) AND LOCATION				
THIS DRAWING IS A CONTROLLED DOCUMENT.				
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN G. ATTADIA - DOCK5 03-24-05 CHK D.L. GORENC 03-24-05 APVD M. WALMSLEY 03-24-05 NAME PRODUCT SPEC APPLICATION SPEC
mm [INCHES]		0 PLC ± - 1 PLC ± - 2 PLC ± 0.13 [005] 3 PLC ± - 4 PLC ± - ANGLES ± -		
MATERIAL	FINISH	WEIGHT	SIZE	RESTRICTED TO
6	7	7.3 GRAMS	A1 00779	
CUSTOMER DRAWING		SCALE	DRAWING NO	REV
		4:1	C=5146099	1 OF 1