

Panel feed-through - QPD W 3PE1,5 0,1 BK RLM5 - 1409122

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Panel feed-through, QUICKON connection, number of positions: 3+PE, 17.5 A, black

RoHS

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
GTIN	 4 046356 862820
GTIN	4046356862820

Technical data

General

Color	black
Connection method	QUICKON connection

Cabel

Position marking	1, 2, 3, PE
------------------	-------------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Temperature when conductor connected	-40 °C ... 50 °C

Electrical characteristics

Nominal current I_N	17.5 A
-----------------------	--------

Material data

Contact material	Cu
Contact surface material	silver-plated
Contact carrier material	PA
Insulating material	PA

Approvals

Approvals

Panel feed-through - QPD W 3PE1,5 0,1 BK RLM5 - 1409122

Approvals

Approvals

GL

Ex Approvals

Approval details

GL		http://exchange.dnv.com/tari/	6195914 HH
----	---	---	------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>