



All rights strictly reserved. Reproduction or issue to third parties in any form
 whatsoever is not permitted without written authority from the proprietor.
 Property of F C I b.v.
 F C I b.v.



NOTES:

- 1 MATERIAL:
THERMOPL. POLYESTER 30% GLASS
FLAME RETARDANT ACC. UL 94-VO
COLOR NATURAL.
- 2 WHEN USING THIS PRODUCT IN A
STRAIGHT TO BOARD APPLICATION
THE FOLLOWING MUST BE TAKEN
INTO ACCOUNT:
-101LF HOUSING IS TO BE USED
FOR THE SOLDER TO BOARD
INSERT 88980-00ZLF.
-111LF HOUSING IS TO BE USED
FOR THE PRESS FIT TO BOARD
INSERT 88978-001LF.

3. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
4. THE HOUSING WILL WITHSTAND EXPOSURE TO 260 DEGREE PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION. WITH A 1.6mm MINIMUM THICK CIRCUIT BOARD.

mat'l. code			tolerances unless otherwise specified			CUSTOMER COPY		 ELECTRONICS www.ficonnect.com	
SEE NOTE 1									
ltr	ecn no	date				projection		title	
A	H10346	DAN 920424	linear					HEADER MINI COAX STRAIGHT 3x3	
B	H20755	DAN 921124							
C	H60040	RVI 960119	angles			mm		product family	
D	H70112	RMA 970218	dr	D Andrews 920424				ETRAL(tm)	
E	H90476	DOB 990816	eng	D Andrews 920424		scale		size dwg no	
F	6608-0436	CLU 051102	chr	P Schalk 200424				A2	
sheet revision			app'd Coolmans 960119			5:1		sheet 1 of 1	