



---

# **GPIO Expander Keypad and LCD Demo Board User's Guide**

---

---

**Note the following details of the code protection feature on Microchip devices:**

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

---

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights.

#### Trademarks

The Microchip name and logo, the Microchip logo, Accuron, dsPIC, KEELOQ, microID, MPLAB, PIC, PICmicro, PICSTART, PRO MATE, PowerSmart, rfPIC and SmartShunt are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AmpLab, FilterLab, Migratable Memory, MXDEV, MXLAB, SEEVAL, SmartSensor and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Analog-for-the-Digital Age, Application Maestro, CodeGuard, dsPICDEM, dsPICDEM.net, dsPICworks, ECAN, ECONOMONITOR, FanSense, FlexROM, fuzzyLAB, In-Circuit Serial Programming, ICSP, ICEPIC, Linear Active Thermistor, Mindi, MiWi, MPASM, MPLIB, MPLINK, PICkit, PICDEM, PICDEM.net, PICLAB, PICtail, PowerCal, PowerInfo, PowerMate, PowerTool, REAL ICE, rfLAB, rfPICDEM, Select Mode, Smart Serial, SmartTel, Total Endurance, UNI/O, WiperLock and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

All other trademarks mentioned herein are property of their respective companies.

© 2006, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

 Printed on recycled paper.

---

**QUALITY MANAGEMENT SYSTEM  
CERTIFIED BY DNV  
= ISO/TS 16949:2002 =**

*Microchip received ISO/TS-16949:2002 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona, Gresham, Oregon and Mountain View, California. The Company's quality system processes and procedures are for its PIC® 8-bit MCUs, KEELOQ® code hopping devices, Serial EEPROMS, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.*



# GPIO EXPANDER KEYPAD AND LCD DEMO BOARD USER'S GUIDE

## Table of Contents

<b>Preface .....</b>	<b>1</b>
Introduction.....	1
Document Layout .....	1
Conventions Used in this Guide .....	2
Recommended Reading.....	2
The Microchip Web Site .....	3
Customer Support .....	3
Document Revision History .....	3
<b>Chapter 1. Product Overview .....</b>	<b>5</b>
1.1 Introduction .....	5
1.2 What is the GPIO Expander Keypad and LCD Demo Board? .....	5
1.3 What The GPIO Expander Keypad and LCD Demo Board Kit Includes .....	5
<b>Chapter 2. Installation and Operation .....</b>	<b>7</b>
2.1 Introduction .....	7
2.2 Features .....	7
2.3 Getting Started .....	8
2.4 GPIO Expander Keypad and LCD Demo Board Description .....	9
2.5 Firmware Description .....	10
<b>Appendix A. Schematics and Board Layouts .....</b>	<b>15</b>
A.1 Introduction .....	15
A.2 Board Schematic - Page 1 .....	16
A.3 Board Schematic - Page 2 .....	17
A.4 Board Schematic - Page 3 .....	18
A.5 Board - Top Layer (with Silk screen) .....	19
A.6 Board - Bottom Layer .....	19
<b>Appendix B. Bill Of Materials (BOM) .....</b>	<b>21</b>
<b>Worldwide Sales and Service .....</b>	<b>24</b>

# **GPIO Expander Keypad and LCD Demo Board User's Guide**

---

---

## **NOTES:**



# GPIO EXPANDER KEYPAD AND LCD DEMO BOARD USER'S GUIDE

## Preface

### NOTICE TO CUSTOMERS

All documentation becomes dated, and this manual is no exception. Microchip tools and documentation are constantly evolving to meet customer needs, so some actual dialogs and/or tool descriptions may differ from those in this document. Please refer to our web site ([www.microchip.com](http://www.microchip.com)) to obtain the latest documentation available.

Documents are identified with a “DS” number. This number is located on the bottom of each page, in front of the page number. The numbering convention for the DS number is “DSXXXXXA”, where “XXXXX” is the document number and “A” is the revision level of the document.

## INTRODUCTION

This chapter contains general information that will be useful to know before using the GPIO Expander Keypad and LCD Demo Board. Items discussed in this chapter include:

- Document Layout
- Conventions Used in this Guide
- Recommended Reading
- The Microchip Web Site
- Customer Support
- Document Revision History

## DOCUMENT LAYOUT

This document describes how to use the GPIO Expander Keypad and LCD Demo Board as a development tool. The manual layout is as follows:

- **Chapter 1. “Product Overview”** – Important information about the GPIO Expander Keypad and LCD Demo Board.
- **Chapter 2. “Installation and Operation”** – Includes instructions on how to get started with this evaluation board.
- **Appendix A. “Schematics and Board Layouts”** – Shows the schematic and layout diagrams for the GPIO Expander Keypad and LCD Demo Board.
- **Appendix B. “Bill Of Materials (BOM)”** – Lists the parts used to build the GPIO Expander Keypad and LCD Demo Board.

## CONVENTIONS USED IN THIS GUIDE

This manual uses the following documentation conventions:

### DOCUMENTATION CONVENTIONS

Description	Represents	Examples
<b>Arial font:</b>		
Italic characters	Referenced books	MPLAB® IDE User's Guide
	Emphasized text	...is the <i>only</i> compiler...
Initial caps	A window	the Output window
	A dialog	the Settings dialog
	A menu selection	select Enable Programmer
Quotes	A field name in a window or dialog	"Save project before build"
Underlined, italic text with right angle bracket	A menu path	<u>File</u> >Save
Bold characters	A dialog button	Click <b>OK</b>
	A tab	Click the <b>Power</b> tab
N'Rnnnn	A number in verilog format, where N is the total number of digits, R is the radix and n is a digit.	4'b0010, 2'hF1
Text in angle brackets < >	A key on the keyboard	Press <Enter>, <F1>
<b>Courier New font:</b>		
Plain Courier New	Sample source code	#define START
	Filenames	autoexec.bat
	File paths	c:\mcc18\h
	Keywords	_asm, _endasm, static
	Command-line options	-Opa+, -Opa-
	Bit values	0, 1
	Constants	0xFF, 'A'
Italic Courier New	A variable argument	<i>file.o</i> , where <i>file</i> can be any valid filename
Square brackets [ ]	Optional arguments	mcc18 [options] <i>file</i> [options]
Curly brackets and pipe character: {   }	Choice of mutually exclusive arguments; an OR selection	errorlevel {0 1}

## RECOMMENDED READING

For more information regarding the Stand-Alone CAN controller, CAN I/O Expander, and CAN transceiver devices, refer to the appropriate data sheet. Table 1 shows the device and associated Data Sheet literature number. These documents can be found at Microchip's web site at: [www.microchip.com](http://www.microchip.com).

**TABLE 1: DEVICES AND DATA SHEET LITERATURE NUMBERS**

Device	Literature #	Device	Literature #
<b>MCP23X08</b>	DS21919	<b>PIC18F4550</b>	DS39632
<b>MCP23X17</b>	DS21952	<b>MCP1702</b>	DS22008

## THE MICROCHIP WEB SITE

Microchip provides online support via our web site at [www.microchip.com](http://www.microchip.com). This web site is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

## CUSTOMER SUPPORT

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support
- Development Systems Information Line

Customers should contact their distributor, representative or field application engineer for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: <http://support.microchip.com>

## DOCUMENT REVISION HISTORY

### Revision A (October 2006)

- Initial Release of this Document.

# **GPIO Expander Keypad and LCD Demo Board User's Guide**

---

---

## **NOTES:**



# GPIO EXPANDER KEYPAD AND LCD DEMO BOARD USER'S GUIDE

## Chapter 1. Product Overview

### 1.1 INTRODUCTION

This chapter provides an overview of the GPIO Expander Keypad and LCD Demo Board and covers the following topics:

- What is the GPIO Expander Keypad and LCD Demo Board?
- What the GPIO Expander Keypad and LCD Demo Board Kit includes

### 1.2 WHAT IS THE GPIO EXPANDER KEYPAD AND LCD DEMO BOARD?

The GPIO Expander Keypad and LCD Demo Board allows the system designer to evaluate the operation of the MCP23X17 and MCP23X08 General Purpose I/O (GPIO) Expanders. The board demonstrates the GPIO Expanders' performance in a keypad and LCD example.

### 1.3 WHAT THE GPIO EXPANDER KEYPAD AND LCD DEMO BOARD KIT INCLUDES

This GPIO Expander Keypad and LCD Demo Board Kit includes:

- One GPIO Expander Keypad and LCD Demo Board (102-00116)
  - MCP23008 GPIO Expander with I<sup>2</sup>C™ interface (installed)
  - MCP23S08 GPIO Expander with SPI interface (installed)
  - MCP23017 GPIO Expander with I<sup>2</sup>C™ interface (installed)
  - MCP23S17 GPIO Expander with SPI interface (installed)
- Analog and Interface Products Demonstration Boards CD-ROM (DS21912)
  - GPIO Expander Keypad and LCD Demo Board User's Guide (DS51636)
  - PIC® Microcontroller Firmware
  - PCB Gerber Files

# **GPIO Expander Keypad and LCD Demo Board User's Guide**

---

---

## **NOTES:**



# GPIO EXPANDER KEYPAD AND LCD DEMO BOARD USER'S GUIDE

## Chapter 2. Installation and Operation

### 2.1 INTRODUCTION

This chapter discusses the setup and operation of the GPIO Expander Keypad and LCD Demo Board.

The GPIO Expander Keypad and LCD Demo Board is designed to demonstrate using GPIO expanders in a keypad and LCD example. The MCP23X17 interfaces to a 2x16 LCD module and the MCP23X08 interfaces to a 4x4 keyed matrix.

Both the I<sup>2</sup>C™ and SPI versions are included on the board to demonstrate both serial interfaces.

### 2.2 FEATURES

The GPIO Expander Keypad and LCD Demo Board has the following features:


- Two (2) 8-bit GPIO Expanders
  - MCP23008 with I<sup>2</sup>C™ interface
  - MCP23S08 with SPI interface
- Two (2) 16-bit GPIO Expanders
  - MCP23017 with I<sup>2</sup>C™ interface
  - MCP23S17 with SPI interface
- 4X4 keypad layout (16 momentary buttons)
  - Numbers 0 - 9
  - Six special function buttons
- A 2X16 LCD module
- Headers for the MCP23X08 and MCP23X17 pins
- Header for programming the PIC18F4550

## 2.3 GETTING STARTED

The GPIO Expander Keypad and LCD Demo Board is a fully functional, assembled and tested board for demonstrating the MCP23008 and MCP23017 ( $I^2C$  interface) and MCP23S08 and MCP23S17 (SPI interface) general purpose I/O expanders. The following describes the basic setup and operation (see [Figure 2-1](#)):

1. Either connect a 9V power supply into the power jack (J2) or connect a 5 V power supply to the  $V_{DD}$  and GND test points.
2. The green power LED will illuminate.
3. The LCD will display the startup splash screen.
4. The appropriate LEDs ( $I^2C$  or SPI) will illuminate to indicate the current serial mode.
5. Pressing buttons:
  - **0 - 9, #, \*:** will be reflected on the LCD
  - **M:** switches modes ( $I^2C$  and SPI) to communicate with the MCP23X17 and MCP23X08; **B:** backspace; **R:** carriage return, and screen clear (2nd press); **S:** space

**FIGURE 2-1: BOARD LAYOUT**




## 2.4 GPIO EXPANDER KEYPAD AND LCD DEMO BOARD DESCRIPTION

### 2.4.1 Major Board Components

The functional block diagram is shown in [Figure 2-2](#).

**FIGURE 2-2: FUNCTIONAL BLOCK DIAGRAM**



1. The **GPIO BLOCK** contains the MCP23X17 and MCP23X08 GPIO Expanders. Two (2) MCP23X17 devices are connected to the LCD module and two (2) MCP23X08 devices are connected to the keypad matrix. A button on the keypad toggles between **I<sup>2</sup>C mode**, the MCP23017 and MCP23008 are controlled by the PIC MCU. When in **SPI mode**, the MCP23S17 and MCP23S08 are controlled. Only one (1) MCP23X08 and one (1) MCP23X17 is on the bus at a time.
2. The **CONTROL BLOCK** contains the PIC18F4550 and is the main intelligence in the system.
3. The **INPUT BLOCK** contains the 4x4 keypad matrix. The MCP23X08 devices are used to scan the keys.
4. The **OUTPUT BLOCK** contains the 2x16 LCD. The MCP23X17 devices control the display.
5. The MCP23X17 and MCP23X08 I/O and serial lines are routed to the **HEADER BLOCK** to allow the pins to be probed.
6. The **PROGRAMMING BLOCK** contains the ICSP™ header for programming/debugging the PIC18F4550.
7. The **POWER BLOCK** contains the MCP1702 5V voltage regulator. The board can be powered by a 9V supply (connected through the power jack) or by applying 5V directly to the power points.

## 2.5 FIRMWARE DESCRIPTION

See [Figure 2-3](#) for the main firmware flow diagram.

### Main Function:

1. The firmware first configures the PIC MCU.
2. The MCP23X08 and MCP23X17 devices are configured. I<sup>2</sup>C Devices are selected first by default. The SPI devices I/O are held in reset.
3. The LCD splash screen is shown.
4. Wait for an interrupt from the MCP23X08. An interrupt will occur when a button is pressed. Four (4) inputs are configured to interrupt on falling edge. These inputs are for the “columns” of the keypad matrix.
5. After the interrupt occurs, the firmware calls the **Scan\_Buttons** routine.
6. Then the **Update\_LCD** routine.


### **Scan\_Buttons** Function:

1. Read INTCAP register. This register contains a snapshot of the port condition when the interrupt occurred.
2. Swap inputs and outputs so the rows can be read.
3. Read GPIO register and merge with variable containing INTCAP value.
4. The pressed key is determined by looking up the result in a lookup table.


### **Update\_LCD** Function:

1. The LCD is updated based on which button was pressed.

**FIGURE 2-3: MAIN FIRMWARE FLOW**




**FIGURE 2-4: KEYPAD SCAN**



# Installation and Operation

FIGURE 2-5: LCD UPDATE



# **GPIO Expander Keypad and LCD Demo Board User's Guide**

---

---

## **NOTES:**



# GPIO EXPANDER KEYPAD AND LCD DEMO BOARD USER'S GUIDE

---

## Appendix A. Schematics and Board Layouts

---


### A.1 INTRODUCTION

This appendix contains the schematic and PCB layout for the GPIO Expander Keypad and LCD Demo Board. Diagrams included:

- Board Schematics - Pages 1 - 3.
- Board - Top Layer (with silk screen)
- Board - Bottom Layer


# GPIO Expander Keypad and LCD Demo Board User's Guide

## A.2 BOARD SCHEMATIC - PAGE 1




## Schematics and Board Layouts

### A.3 BOARD SCHEMATIC - PAGE 2




## A.4 BOARD SCHEMATIC - PAGE 3




# Schematics and Board Layouts

## A.5 BOARD - TOP LAYER (WITH SILK SCREEN)



## A.6 BOARD - BOTTOM LAYER



# **GPIO Expander Keypad and LCD Demo Board User's Guide**

---

---

## **NOTES:**



# GPIO EXPANDER KEYPAD AND LCD DEMO BOARD USER'S GUIDE

## Appendix B. Bill Of Materials (BOM)

**TABLE B-1: BILL OF MATERIALS**

Qty	Reference Designator	Description	Manufacturer	Part Number
23	C1, C5, C6 C15, C25, C30, C31, C32, C33, C34, C35, C36, C37, C38, C39, C40, C41, C42, C43, C44, C45, C46, C47, C48	CAP 1UF 16V CERAMIC Y5V 0805	Panasonic® - ECG	ECJ-2VF1C105Z
1	C3	CAP CER .33UF 16V Y5V 0805	Murata Electronics® North America	GRM219F51C334ZA01D
2	C16, C17	CAP 22PF 50V CERM CHIP 0805 SMD *Do Not Populate*	Panasonic - ECG	ECJ-2VC1H220J
1	C18	CAP .22UF 16V CERAMIC X7R 0805	Panasonic - ECG	ECJ-2VB1C224K
4	D1, D2, D3, D4	LED 636NM SUPER RED 0805 SMD	LITE-ON INC	SML-LX0805SIC-TR
2	D5, D6	DIODE SCHOTTKY 20V 0.5A SOD123	ON Semiconductor®	MBR0520LT1G
2	D7, D8	LED THIN 565NM GRN DIFF 0805 SMD	Optoelectronics	SML-LXT0805GW-TR
1	D9	RECT SCHOTTKY 1A 20V DO-214AA	Micro Commercial Co.	SMB5817-TP
4	EA Corner	BUMPON X-TALL TAPER SQ .81X.30BK	3M/ESM	SJ-5523 (BLACK)
1	J1	*Do Not Populate*	—	—
1	J2	CONN POWER JACK 2.5MM PCB CIRC	CUI Inc	PJ-102B
1	J3	*Do Not Populate*	—	—
1	J4	*Do Not Populate*	—	—
2	J5, J10	*Do Not Populate*	—	—
1	J9	CONN USB RTANG FEMALE TYPE B PCB *Do Not Populate*	Assmann Electronics Inc	AU-Y1007-R
1	LCD1	LCD_2x16	Fema	CG1626-SGR1
6	R1, R2, R3, R8, R9, R53	RES 10.0K OHM 1/10W 1% 0805 SMD	Panasonic - ECG	ERJ-6ENF1002V
2	R4, R5	RES 270 OHM 1/8W 5% 0805 SMD	Panasonic - ECG	ERJ-6GEYJ271V
1	R6	RES 523 OHM 1/8W 1% 0805 SMD	Yageo® Corporation	RC0805FR-07523RL
2	R7, R54	RES 4.70K OHM 1/8W 1% 0805 SMD	Yageo Corporation	RC0805FR-074K7L
3	R24, R25, R35	RES 1.00K OHM 1/10W 1% 0805 SMD	Panasonic - ECG	ERJ-6ENF1001V
2	R29, R30	RES 0.0 OHM 1/8W 5% 0805 SMD	Panasonic - ECG	ERJ-6GEY0R00V

**Note 1:** The components listed in this Bill of Materials are representative of the PCB assembly. The released BOM used in manufacturing uses all RoHS-compliant components.

# GPIO Expander Keypad and LCD Demo Board User's Guide

---

**TABLE B-1: BILL OF MATERIALS (CONTINUED)**

Qty	Reference Designator	Description	Manufacturer	Part Number
16	R32, R33, R34, R36, R37, R38, R39, R40, R41, R42, R43, R44, R45, R46, R47, R48	RES 100 OHM 1/10W 3900PPM 5%0805	Panasonic - ECG	ERA-S39J101V
1	R49	RES 33.2K OHM 1/8W 1% 0805 SMD	Yageo® Corporation	RC0805FR-0733K2L
2	R50, R52	RES 475 OHM 1/10W 1% 0603 SMD	Panasonic - ECG	ERJ-3EKF4750V
1	R51	RES 100K OHM 1/8W 5% 0805 SMD	Panasonic - ECG	ERJ-6GEYJ104V
17	S11, S12, S13, S14, S15, S16, S17, S18, S19, S20, S21, S22, S23, S24, S25, S26, S27	SWITCH TACT 6MM SMD MOM 160GF	Omron Electronics Inc	B3S-1000
1	TP1	TEST POINT PC MULTI PURPOSE BLK	Keystone Electronics®	5011
1	TP2	TEST POINT PC MULTI PURPOSE RED	Keystone Electronics	5010
1	U1	16 Bit I/O Expander with Serial Interface	Microchip Technology Inc	MCP23S17-E/SS
1	U2	8-Bit I/O Expander with SPI Interface	Microchip Technology Inc	MCP23S08-E/SS
1	U3	16 Bit I/O Expander with Serial Interface	Microchip Technology Inc	MCP23017-E/SS
1	U4	8-Bit I/O Expander with I <sup>2</sup> C Interface	Microchip Technology Inc	MCP23008-E/SS
1	U5	44-Pin, High-Performance, Enhanced Flash, USB Microcontroller	Microchip Technology Inc	PIC18F4550
1	U6	2 µA Low Dropout Positive Voltage Regulator	Microchip Technology Inc	MCP1702T-5002I/CB
1	U7	MOSFET P-CH 20V 850MA SSOT3	Fairchild Semiconductor®	NDS352P
1	Y1	CRYSTAL 20.0000 MHZ SERIES RES *Do Not Populate*	CTS-Frequency Controls	ATS200

**Note 1:** The components listed in this Bill of Materials are representative of the PCB assembly. The released BOM used in manufacturing uses all RoHS-compliant components.

# **Bill Of Materials (BOM)**

---

**NOTES:**



# MICROCHIP

## WORLDWIDE SALES AND SERVICE

### AMERICAS

**Corporate Office**  
2355 West Chandler Blvd.  
Chandler, AZ 85224-6199  
Tel: 480-792-7200  
Fax: 480-792-7277  
Technical Support:  
<http://support.microchip.com>  
Web Address:  
[www.microchip.com](http://www.microchip.com)

**Atlanta**

Alpharetta, GA  
Tel: 770-640-0034  
Fax: 770-640-0307

**Boston**

Westborough, MA  
Tel: 774-760-0087  
Fax: 774-760-0088

**Chicago**

Itasca, IL  
Tel: 630-285-0071  
Fax: 630-285-0075

**Dallas**

Addison, TX  
Tel: 972-818-7423  
Fax: 972-818-2924

**Detroit**

Farmington Hills, MI  
Tel: 248-538-2250  
Fax: 248-538-2260

**Kokomo**

Kokomo, IN  
Tel: 765-864-8360  
Fax: 765-864-8387

**Los Angeles**

Mission Viejo, CA  
Tel: 949-462-9523  
Fax: 949-462-9608

**Santa Clara**

Santa Clara, CA  
Tel: 408-961-6444  
Fax: 408-961-6445

**Toronto**

Mississauga, Ontario,  
Canada  
Tel: 905-673-0699  
Fax: 905-673-6509

### ASIA/PACIFIC

**Asia Pacific Office**  
Suites 3707-14, 37th Floor  
Tower 6, The Gateway  
Habour City, Kowloon  
Hong Kong  
Tel: 852-2401-1200  
Fax: 852-2401-3431

**Australia - Sydney**  
Tel: 61-2-9868-6733  
Fax: 61-2-9868-6755

**China - Beijing**  
Tel: 86-10-8528-2100  
Fax: 86-10-8528-2104

**China - Chengdu**  
Tel: 86-28-8665-5511  
Fax: 86-28-8665-7889

**China - Fuzhou**  
Tel: 86-591-8750-3506  
Fax: 86-591-8750-3521

**China - Hong Kong SAR**  
Tel: 852-2401-1200  
Fax: 852-2401-3431

**China - Qingdao**  
Tel: 86-532-8502-7355  
Fax: 86-532-8502-7205

**China - Shanghai**  
Tel: 86-21-5407-5533  
Fax: 86-21-5407-5066

**China - Shenyang**  
Tel: 86-24-2334-2829  
Fax: 86-24-2334-2393

**China - Shenzhen**  
Tel: 86-755-8203-2660  
Fax: 86-755-8203-1760

**China - Shunde**  
Tel: 86-757-2839-5507  
Fax: 86-757-2839-5571

**China - Wuhan**  
Tel: 86-27-5980-5300  
Fax: 86-27-5980-5118

**China - Xian**  
Tel: 86-29-8833-7250  
Fax: 86-29-8833-7256

### ASIA/PACIFIC

**India - Bangalore**  
Tel: 91-80-4182-8400  
Fax: 91-80-4182-8422

**India - New Delhi**  
Tel: 91-11-4160-8631  
Fax: 91-11-4160-8632

**India - Pune**  
Tel: 91-20-2566-1512  
Fax: 91-20-2566-1513

**Japan - Yokohama**  
Tel: 81-45-471-6166  
Fax: 81-45-471-6122

**Korea - Gumi**  
Tel: 82-54-473-4301  
Fax: 82-54-473-4302

**Korea - Seoul**  
Tel: 82-2-554-7200  
Fax: 82-2-558-5932 or  
82-2-558-5934

**Malaysia - Penang**  
Tel: 60-4-646-8870  
Fax: 60-4-646-5086

**Philippines - Manila**  
Tel: 63-2-634-9065  
Fax: 63-2-634-9069

**Singapore**  
Tel: 65-6334-8870  
Fax: 65-6334-8850

**Taiwan - Hsin Chu**  
Tel: 886-3-572-9526  
Fax: 886-3-572-6459

**Taiwan - Kaohsiung**  
Tel: 886-7-536-4818  
Fax: 886-7-536-4803

**Taiwan - Taipei**  
Tel: 886-2-2500-6610  
Fax: 886-2-2508-0102

**Thailand - Bangkok**  
Tel: 66-2-694-1351  
Fax: 66-2-694-1350

### EUROPE

**Austria - Wels**  
Tel: 43-7242-2244-39  
Fax: 43-7242-2244-393

**Denmark - Copenhagen**  
Tel: 45-4450-2828  
Fax: 45-4485-2829

**France - Paris**  
Tel: 33-1-69-53-63-20  
Fax: 33-1-69-30-90-79

**Germany - Munich**  
Tel: 49-89-627-144-0  
Fax: 49-89-627-144-44

**Italy - Milan**  
Tel: 39-0331-742611  
Fax: 39-0331-466781

**Netherlands - Drunen**  
Tel: 31-416-690399  
Fax: 31-416-690340

**Spain - Madrid**  
Tel: 34-91-708-08-90  
Fax: 34-91-708-08-91

**UK - Wokingham**  
Tel: 44-118-921-5869  
Fax: 44-118-921-5820