

Cable gland - G-INS-M63-L68L-PNES-BK - 1411139

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Polyamide 6, External cable diameter 34 mm ... 44 mm, Shielding: No, Connecting thread: M63, Color: jet black

The illustration shows version G-INS-M25-M68N-PNES-BK

Product Features



Key commercial data

Packing unit	1 pc
Custom tariff number	39269097
Country of origin	Turkey

Technical data

Dimensions

Length	75.4 mm
Length without connecting thread	57.4 mm
Connecting thread diameter	63 mm
Wrench size, union nut	65 mm
Wrench size, support	65 mm
Hexagon angular dimension GRP	72.2 mm
Length of the connecting thread	18 mm
External cable diameter	34 mm ... 44 mm

Ambient conditions

Degree of protection	IP68
	IP68 (5 bar, 30 min.)
Ambient temperature (operation)	-30 °C ... 80 °C (for a short period up to 150 °C)

Cable gland - G-INS-M63-L68L-PNES-BK - 1411139

Technical data

General

Cable gland material	Polyamide 6
Seal material	Neoprene
Cable seal material	Neoprene
Shielded	No
Thread type on connection side	M63
Torque	20 Nm ... 25 Nm
Inflammability class according to UL 94	V2
Color	jet black RAL 9005
	jet black

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

CSA / UL Listed / VDE Zeichengenehmigung

Ex Approvals

Approvals submitted

Approval details

Cable gland - G-INS-M63-L68L-PNES-BK - 1411139

Approvals

CSA 

UL Listed 

VDE Zeichengenehmigung 

Drawings

Dimensional drawing

