

SIGN	DATE	DESCRIPTION	APPROVER
△	02/27/07	Part No. is changed.	Aaron
△	10/13/11	Operating temperature is changed	ChenMing
△	10/13/11	Remove the "VDE" mark	ChenMing
△	10/13/11	The dimension is changed from 22.90 to 22.9	ChenMing
△		THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!	

Material

- Item 1 Insulating body Thermoplastic (UL94V-0)
- Item 2 Contacts PIN PhBz(CuSn) Tin plated

Electrica

- Voltage rating: 300VAC
- Current rating: 2A
- Solid wire(AWG): 18
- Stranded wire(AWG): 18
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- △ ● Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- △ ● Safety Approval:
- Critical dimension: ▽

△ TN 06 2 x 1 0 xxxx G

0 Black
9 White


RoHS compliant
(lead<4%)
In copper Alloy





0000 Standard @ Logo
000A Standard ANY Logo
Any special item by
customer request,
please contact sales
department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TN-4.5mm 180D Series 6P Without cover				
PART NO.	TN062X10XXXXG				DWG NO.	8TN0202
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
			ChenMing 2011.10.13		UNIT: mm	X. ±0.50
					SCALE: NONE	X.X ±0.30
					REVISION: D	X.XX ±0.10
SHEET: 01/01				REV.: D		



P.C.B LAYOUT

