

Printed-circuit board connector - IPC 5/ 2-G-7,62-XW GY - 1701283

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB headers, nominal current: 41 A, number of positions: 2, pitch: 7.62 mm, color: gray, contact surface: Tin, mounting: Wave soldering

The figure shows a 5-pos. version of the product

Your advantages

- ✓ Well-known mounting principle allows worldwide use
- ✓ Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- ✓ Inverted header with socket contacts for touch-proof device outputs or PCB/PCB connections
- ✓ Integrated double steel spring provides additional safety in the event of temperature and power fluctuations



Key Commercial Data

Packing unit	50 pc
GTIN	
GTIN	4046356524438

Technical data

Dimensions

Pitch	7.62 mm
Dimension a	7.62 mm
Height	12.8 mm
Length of the solder pin	5 mm
Pin dimensions	0.8 x 1.2 mm

General

Range of articles	IPC 5/...-G
Rated voltage (III/3)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	41 A

Printed-circuit board connector - IPC 5/ 2-G-7,62-XW GY - 1701283

Technical data

General

Color	gray
Number of positions	2

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC / cULus Recognized

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19920722
	D	B	C
Nominal voltage UN	600 V	300 V	300 V
Nominal current IN	5 A	41 A	41 A

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>