


SIGN	DATE	DESCRIPTION	APPROVER
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			



- Material:
- Item ① Insulator(housing): Thermoplastic (UL94V-0)
 - Item ② Wire guard: Stainless steel
 - Item ③ Terminal Body(contact pin): Copper.Tin platd
 - Item ④ Insulator(Cover): Thermoplastic (UL94V-0)

Electrical:	cULus	IEC
● Voltage rating:	300V	250V
● Current rating:	37A	76A
● Wire range:	0.2-16 mm ²	
● Solid wire(AWG):	6-24	
● Stranded wire(AWG):	6-24	
● Wire strip length:	12-13mm	
● Withstanding Voltage:	1.6KV	4KV
● Operating temperature:	-40°C to +115°C	
● Soldering temperature:	250°C±10°C/5 Sec	
● Safety Approval:		

H8 xx 0 0 x 0 xxxx G

No. OF POLES
02: 2 POLES
:
:
12: 12POLES

COLOR
0: BLACK
5: GREEN
6: BLUE
8: GREY

G: Pb<40000ppm
0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

PCB Layout

POLE		2	3	4	5	6	7	8	9	10	11	12
A		20.00	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00	120.00
B		10.00	20.00	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00
Tol.	±0.15						±0.25					
POLE	13	14	15	16	17	18	19	20	21	22	23	24
A	130.00	140.00	150.00	160.00	170.00	180.00	190.00	200.00	210.00	220.00	230.00	240.00
B	120.00	130.00	140.00	150.00	160.00	170.00	180.00	190.00	200.00	210.00	220.00	230.00
Tol.	±0.35						±0.50					

ANYTEK

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

CUSTOMER COPY

TITLE	H8 10.0mm Series				DWG NO.	8H80001		
PART NO.	H8xx00x0xxxxG				DWG NO.	8H80001		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.				Tolerance
		Runner 2010.10.15	Tony 2007.06.21		UNIT: mm	X. ±0.50		
					SCALE: NONE	X.X ±0.30		
						X.XX ±0.10		
						X° ±1°		
SHEET: 01/01		REV.: B						