

Relay Module - BC 17 REL-S/MSTB/R3,3K/R680 - 2900116


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Relay module, standard interface for fire alarm systems, with a firmly soldered miniature relay, 1 N/C contact, input voltage: 24 V DC



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 046356 473705
GTIN	4046356473705

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	17.8 mm
Height	90 mm
Depth	61 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

Coil side

Nominal input voltage U_N	24 V DC
Input voltage range in reference to U_N	0.8 ... 1.1
Typical input current at U_N	10 mA
Protective circuit	Bridge rectifier Bridge rectifier, varistor
	Capacitor Capacitor
Operating voltage display	LED

Relay Module - BC 17 REL-S/MSTB/R3,3K/R680 - 2900116

Technical data

Contact side

Contact type	1 N/C contact
Contact material	AgSnO ₂ , gold-plated
Note	A 680 Ω resistor is connected in series and a 3.3 k Ω resistor is connected parallel to the output
Maximum switching voltage	30 V AC
Limiting continuous current	max. 3 A

General

Degree of protection	IP20
Mounting position	any
Assembly instructions	In rows with zero spacing

Standards and Regulations

Designation	Air clearances and creepage distances, input/output
Standards/regulations	EN 50178
Rated insulation voltage	250 V
Rated surge voltage/insulation	Basic insulation
Rated surge voltage	4 kV (1.2/50 μ s)
Degree of pollution	2
Overvoltage category	III

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>