



**Mallory Sonalert Products, Inc.**

Part #:

**SC2036ACP**

## Sales Outline Drawing


Revision:

**C**

### Specifications:

|                       |                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------|
| Sound Level Category  | Medium                                                                                     |
| Mode of Operation     | Single Pulse, Chime                                                                        |
| Voltage Rating        | 30 to 110 VAC/DC                                                                           |
| Frequency             | 1000 $\pm$ 100 Hz                                                                          |
| Loudness @ 2 FT       | 70 to 81 dB(A) Typ.                                                                        |
| Loudness @ Min Vdc    | 55 dB(A) @ 2 Feet and 30 Vac/dc                                                            |
| Loudness @ Max Vdc    | 75 dB(A) @ 2 Feet and 110 Vac/dc                                                           |
| Current Draw          | 30mA MAX                                                                                   |
| Housing Material      | 6/6 Nylon, Color: Black                                                                    |
| Storage Temperature   | -40° to +85° C                                                                             |
| Operating Temperature | -30° to +65° C                                                                             |
| Panel Mounting        | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |
| Knurled Nut           | Used to attach part to panel. The max recommended torque is 10 in-lbs.                     |
| Weight (Typical)      | 1.8 oz (51g)                                                                               |
| NEMA 3R, 4X, & 12     | Approved with use of ACC03.                                                                |
| Options               | Please contact factory.                                                                    |

### Dimensions: Inches (mm)



MOUNTING: REMOVE BLACK PLASTIC NUT AND INSERT THREADED FRONT THROUGH 1.25" HOLE PUNCHED IN PANEL, IF ORIENTATION IS NEEDED, NOTE LOCKING FLATS ON DRAWING. SCREW NUT BACK ON. DO NOT OVERTIGHTEN.

