



Quality Products. Service Excellence.

20 Amp Heavy Duty Outlet Strip 1589 Series


Features



- Built to meet the rugged requirements of industrial and commercial use.
- All metal housing – tough extruded aluminum case with black powder-coated steel cover.
- Available with on/off switch or red pilot light to indicate power on.
- Mounting feet (with keyhole slots) allow temporary work station mounting if desired.

Specifications

- Heavy-duty black receptacles rated for 20A, 125VAC service (NEMA 5-20R, Single T-Slot).
- Heavy-duty power cord – 12/3 SJT for extreme temperature ranges.
- Integral molded plug with straight blade (NEMA 5-20P) or locking (NEMA L5-20P) configuration.
- Includes 20A, 125VAC circuit breaker to prevent accidental line overload.
- CSA certified, Standards C22.2 (No. 21-95 and No. 42-99).
- UL/cUL Listed Standard UL1363 file No. E166039 & CSA C22.2 No. 308-14



Accessories

- Rack Cabinet Vertical Mount Adaptor

| On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Outlet Qty | Outlet NEMA Type | Cord Length (ft) | Plug Type | Plug NEMA Type |
|---------------------------|---------------------------------------|--------------------|-------|--------|---------------|---------------------|---------------------|--------------|-------------------|
| | | Height | Width | Length | | | | | |
| 1589H4C1 | 1589T4C1 | 2.33 | 2.13 | 10.18 | 4 | 5-20R | 6 | Locking | L5-20P |
| 1589H4D1 | 1589T4D1 | 2.33 | 2.13 | 10.18 | 4 | 5-20R | 15 | Locking | L5-20P |
| 1589H4F1 | 1589T4F1 | 2.33 | 2.13 | 10.18 | 4 | 5-20R | 6 | Straight | 5-20P |
| 1589H4G1 | 1589T4G1 | 2.33 | 2.13 | 10.18 | 4 | 5-20R | 15 | Straight | 5-20P |
| 1589H6C1 | 1589T6C1 | 2.33 | 2.13 | 13.36 | 6 | 5-20R | 6 | Locking | L5-20P |
| 1589H6D1 | 1589T6D1 | 2.33 | 2.13 | 13.36 | 6 | 5-20R | 15 | Locking | L5-20P |

| On/Off Switch Part No. | Illuminated Light Only Part No. | Overall Dimensions | | | Outlet Qty | Outlet NEMA Type | Cord Length (ft) | Plug Type | Plug NEMA Type |
|---------------------------|---------------------------------------|--------------------|-------|--------|---------------|---------------------|---------------------|--------------|-------------------|
| | | Height | Width | Length | | | | | |
| 1589H6F1 | 1589T6F1 | 2.33 | 2.13 | 13.36 | 6 | 5-20R | 6 | Straight | 5-20P |
| 1589H6G1 | 1589T6G1 | 2.33 | 2.13 | 13.36 | 6 | 5-20R | 15 | Straight | 5-20P |
| 1589H8C1 | 1589T8C1 | 2.33 | 2.13 | 16.51 | 8 | 5-20R | 6 | Locking | L5-20P |
| 1589H8D1 | 1589T8D1 | 2.33 | 2.13 | 16.51 | 8 | 5-20R | 15 | Locking | L5-20P |
| 1589H8F1 | 1589T8F1 | 2.33 | 2.13 | 16.51 | 8 | 5-20R | 6 | Straight | 5-20P |
| 1589H8G1 | 1589T8G1 | 2.33 | 2.13 | 16.51 | 8 | 5-20R | 15 | Straight | 5-20P |

Replacement Mounting Foot (One Foot)

| | |
|----------|--------|
| Part No. | 1584MF |
|----------|--------|

Data subject to change without notice

© 2020. Hammond Manufacturing Ltd. All rights reserved.