

| | |
|---------------|-------------------|
| PAIR | CONSIST OF : |
| BTO-26732-D55 | (2) BTO-26740-D55 |

BOTH MICROPHONES OF THE PAIR ARE TESTED TO BTO-26740-D55 SHT 2.1 AND THEN MATCHED TO THE OTHER MICROPHONES USING THE SPECIFICATION AND CONDITIONS BELOW:

| FREQUENCY | TEST TYPE | RANGE OF DEVIATION BETWEEN MICROPHONES | UNITS |
|-----------|-------------|--|---------|
| 1 kHz | SENSITIVITY | 2.0 MAX. | dB |
| 200 Hz | PHASE | 1.5 MAX. | DEGREES |
| 5000 Hz | PHASE | 5.0 MAX. | DEGREES |
| 7000 Hz | SENSITIVITY | 1.0 MAX. | dB |

NOTES:

- DC SUPPLY VOLTAGE 0.9 VOLTS.
- SENSITIVITY AND PHASE VALUES INDICATED ARE VALID AT 50% RH.

3 >>> SHOWS MICROPHONE WITH GREATER RESPONSE PHASE VALUE AT 200 Hz.



| Revision | C.O. # | Implementation Date | RELEASE LEVEL | REVISION |
|----------|------------|---------------------|---------------|----------|
| C | M10101428 | 4-23-07 | Released | C |
| B | M10101231 | 9-14-06 | | |
| A | M10100999P | 1-17-06 | | |

KNOWLES ELECTRONICS
ITASCA, ILLINOIS U.S.A.

WHEN TEST LIMITS ARE USED TO ESTABLISH INCOMING INSPECTION ACCEPTANCE/REJECTION CRITERIA, CORRELATION OF TEST EQUIPMENT WITH KNOWLES IS ALSO REQUIRED FOR ELIMINATION OF EQUIPMENT AND TEST METHOD VARIATION

TITLE: **MICROPHONE PAIR** **BTO-26732-D55**
PERFORMANCE SPECIFICATION **SHT 2.1**

| DR. BY | DATE |
|---------|---------|
| MMM | 1-17-06 |
| CK. BY | DATE |
| GJP | 1-19-06 |
| APP. BY | DATE |
| GJP | 1-19-06 |