





Splice Closures & Sheath Repair

Bonding & Grounding Hardware - Clips & Clamps

Six Ground Clip



A one-piece clip designed for termination of No. 6 copper wire. Fits over ground posts up to $\frac{1}{4}$ inch O.D.

Design Features:

- "L" channel clamps ground wire at a 90-degree angle to minimize danger of pullout
- Clip will withstand a 1000 amp current surge for 20 seconds

Part Number	Description	Inner Pack	Outer Pack	Min Order QTY
C4045	Six Ground Clip	100	2100	100

G Protector Clip



The one-piece clip, bonds or grounds the shield of a service wire or small cable up to ¼" O.D. or 3/8" O.D. at station protectors, pedestals and similar terminations. Low resistance path to ground prevents stray electromagnetic interference from inducing noise or cross talk on cable pairs and provides a ground circuit path from the shield to the ground protector.

Design Features:

- Plastic boot is included to protect shield against corrosion and the environment
- Easy slip-on installation
- Center groove grips cable or buried service drop allowing pairs to fan out from both sides
- Tangs compress against shield for positive electrical and mechanical bond

Basic Kit Contents:

One piece clip Instructions Insulator boot

Part Number	Description	Max Shield O.D	Inner Pack	Outer Pack	Min Order QTY
C4047	G Protector Clip	1/4"	100	1000	100
C4058	G Protector Clip	3/8"	100	1000	100

Eleven X Connector Aluminum



The slotted screw with knurled nut provides effective shield bonding of large aircore and filled service wires up to ½" shield O.D. (11, 16 and 25 pairs) to a ground wire or ground stud. Can also be used to bond the two pieces of butt spliced service drop within a buried service drop closure.

Part Number	Description	Max Shield O.D	Inner Pack	Outer Pack	Min Order QTY
C4066	Eleven X Connector	1/2"	100	1000	100