

THIS DRAWING IS UNPUBLISHED.		RELEASED FOR PUBLICATION		480708 480708	
(C) COPYRIGHT 480708By -		ALL RIGHTS RESERVED.			

LOC		DIST		REVISIONS					
CM	00	P	LTR	DESCRIPTION		DATE	DWN	APVD	
		AP3	REVISED PER ECR-17-008392	28JUN2017	BW	KR			

1

2

3

4

5

6

7

8

9

10

11

12

AMP

SEE DETAIL A

(27.43)
[1.080]

11.68
[.460]

27.43
[1.080]

5

20.32
[.800]

26.67
[1.050]

DETAIL A
OPTIONAL CONSTRUCTION

3-DIMENSIONAL MODEL
NTS

1

MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK™ CAP OR HEADER.

2

SMALL NICKS ARE PERMITTED ON THE CIRCUIT TOWERS WHICH COULD INCREASE THE INITIAL HOUSING MATING FORCE BY UP TO 4.4 NEWTONS [1.0 LBS]. NO INDIVIDUAL NICKED TOWER SHALL INCREASE THIS FORCE BY OVER 2.2 NEWTONS [.5 LBS].

3

DIMENSIONS SHOWN REPRESENT PRODUCT IN DRY, AS MOLDED, CONDITION. ADDITIONAL 2% GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

4

FOUR RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION. NO RIBS OR SIX RIBS EQUALLY SPACED, NO SPECIFIC ORIENTATION, OPTIONAL.

5

UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE EACH ON SIDE OF HOUSING.

6






OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

6	OBSOLETE	BLACK	1-480708-9
		GREY	1-480708-8
		BLUE	1-480708-6
		GREEN	1-480708-5
		YELLOW	1-480708-4
6	OBSOLETE	ORANGE	1-480708-3
		RED	1-480708-2
6	SUPERSEDED BY	BROWN	1-480708-1
		NATURAL	1-480708-0
		COLOR	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER 01SEP04	TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK S. RIDGILL 01SEP04	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S. RIDGILL 01SEP04	PRODUCT SPEC	
0. PLC ± -		APPLICATION SPEC		
1. PLC ± -		SIZE		
2. PLC ± 0.13 [0.005]		CAGE CODE		
3. PLC ± -		DRAWING NO		
4. PLC ± -		RESTRICTED TO		
ANGLES ± ± 0°30'		A1 00779 480708		
FINISH -		WEIGHT		
MATERIAL NYLON, UL 94V-2		CUSTOMER DRAWING		
		SCALE 4:1		
		SHEET 1 OF 2		
		REV AP3		

LOC		DIST		REVISIONS					
CM	00	P	LTR	DESCRIPTION			DATE	DWN	APVD
		--	--	SEE SHEET 1			--	--	--

- 1
- 2
- 3
- STAMP NUMBERS 3.18 HIGH AT WIRE END OF HOUSING (12 POINT DAVID TYPE).
- CHARACTERS TO BE POSITIONED ON HOUSING TO BE READ FROM WIRE END ONLY.
- VIOLET,BLACK,BROWN,AND BLUE COLORED BLOCKS TO BE STAMPED WITH WHITE CHARACTERS. ALL OTHER COLORED BLOCKS TO BE STAMPED WITH BLACK CHARACTERS.



NATURAL	2-480708-0
COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER	01SEP04		 TE Connectivity			
		CHK S. RIDGILL	01SEP04					
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD S. RIDGILL	01SEP04		NAME			
		PRODUCT SPEC		PLUG, 12 CIRCUIT, UNIVERSAL MATE-N-LOK				
	0. PLC 1. PLC 2. PLC 3. PLC 4. PLC ANGLES FINISH	APPLICATION SPEC		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO	
		WEIGHT		A1		00779	C=480708	—
MATERIAL NYLON, UL 94V-2		CUSTOMER DRAWING		SCALE 4:1		SHEET 2 OF 2	REV. AP.3	