



## Main

|                   |  |
|-------------------|--|
| Device short name | XCSL   |
| Enclosure type    | Enclosure water resistant indoor/outdoor<br>Enclosure dustproof indoor/outdoor<br>Enclosure ice/sleet proof indoor/outdoor |

## Complementary

|                               |  |
|-------------------------------|--|
| Line Rated Current            | 10 A   |
| [Us] rated supply voltage     | 24 V DC  |
| Actuator                      | Key  |
| Contact operation             | Slow-break, break before make                            |
| Contacts type and composition | 2 NC<br>1 NO staggered                                   |
| Depth                         | 1.73 in  |
| Enclosure material            | Metal  |
| Height                        | 7.64 in  |
| Installation direction        | Front actuator supply<br>Left electromagnet connection   |
| Key locking position          | Front  |
| Locking options description   | With locking of actuator, unlocking by key operated lock |
| Number of poles               | 3  |
| Permissible voltage           | <= 300 V AC  |
| Pilot light                   | LED orange   |

## Environment

|                                       |                 |
|---------------------------------------|-----------------|
| ambient air temperature for operation | -13...158 °F    |
| IP degree of protection               | IP67            |
| NEMA degree of protection             | NEMA 1/2/3/4/12 |

## Offer Sustainability

|  |  |
|--|--|
| Green Premium product  | Green Premium product  |
| Compliant - since 1136 - Schneider Electric declaration of conformity  | Compliant - since 1136 - Schneider Electric declaration of conformity  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold  |
| Need no specific recycling operations  | Need no specific recycling operations  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.