

RAFIX 22 QR - Emergency stop pushbutton

1.30.243.501/0300

Included: Ring nut with claw.



Switching position indication: In the non-operated condition, a green ring is visible on the side.

General information

| | |
|-------------------|------------|
| Actuator | mushroom |
| Color of mushroom | opaque red |
| Form of collar | round |

Dimensions

| | |
|---|-----------|
| Dimensions of collar | ø 29.8 mm |
| Overall height | 40.1 mm |
| Mounting depth with contact block without cable | 56.4 mm |
| Mounting hole | ø 22.3 mm |
| Mounting grid | - mm |

Mechanical design

| | |
|------------------|-----------------------|
| Mounting | ring nut |
| Contact function | latching |
| Illuminability | no |
| Reset | by clockwise rotation |
| Lock type | - |

Mechanical characteristics

| | |
|----------------------|-------------------------------------|
| Operating force max. | approx. 5 N for 1 switching element |
| Robustness max. | 100 N |
| Robustness | acc. to IEC 60947-5-5 |

Other specifications

| | |
|--------------------------------------|--|
| Operating life (operations) | 100,000 cycle |
| Degree of protection from front side | IP65 (DIN EN 60529) |
| Ambient temp. operating min. | -25 °C |
| Ambient temp. operating max. | +70 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +80 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out to IEC 60947-5-1

