


ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Numbers: PPC7-PPC29
Spec Number: PPC
Page 1 of 1 Pages

Issue: 1
Issue Date: 11/01/2017
Effective Date: 11/13/2017

A. Technical Details

- 1) Material
 - a) Body PA 6 (Polyamide 6)
 - b) Cap PA 6 (Polyamide 6)
 - c) Seal CR (Chloroprene Rubber)
- 2) Color
 - a) Gray, RAL 7001
- 3) Protection Class
 - a) IP 68 5 Bar, 30 min
 - b) IP 66
- 4) Flammability
 - a) V2 (According to UL94)
- 5) Temperature Rating
 - a) Permanent -20°C to +100°C
 - b) Intermittent -30°C to +150°C
- 6) Thread Type
 - a) PG according to DIN 40430
- 7) Approvals
 - a) UL UL 514
 - b) CSA CSA C22.2



| Size | Clamping Range Ø min-max | | Thread Length TL | | Thread Ø TD | | Spanner Width | | | | Outer Ø D | | Max. Height H | | Part Number |
|---------|-----------------------------|-------------|---------------------|-------|----------------|-------|---------------|-------|---------|-------|--------------|-------|------------------|-------|-------------|
| | mm | inch | mm | inch | mm | inch | SW CAP | | SW BODY | | mm | inch | mm | inch | |
| PG 7 | 3,0-6,5 | 0.118-0.256 | 8 | 0.315 | 12,5 | 0.492 | 15 | 0.591 | 15 | 0.591 | 16,9 | 0.665 | 22,0 | 0.866 | PPC7 |
| PG 9 | 4,0-8,0 | 0.157-0.315 | 8 | 0.315 | 15,2 | 0.598 | 19 | 0.748 | 19 | 0.748 | 21,9 | 0.862 | 26,5 | 1.043 | PPC9 |
| PG 11 | 5,0-10,0 | 0.197-0.394 | 8 | 0.315 | 18,6 | 0.732 | 22 | 0.866 | 22 | 0.866 | 25,0 | 0.984 | 29,0 | 1.142 | PPC11 |
| PG 13.5 | 6,0-12,0 | 0.236-0.472 | 10 | 0.394 | 20,4 | 0.803 | 24 | 0.945 | 24 | 0.945 | 27,0 | 1.063 | 29,0 | 1.142 | PPC13 |
| PG16 | 10,0-14,0 | 0.394-0.551 | 10 | 0.394 | 22,5 | 0.886 | 27 | 1.063 | 27 | 1.063 | 30,9 | 1.216 | 31,0 | 1.22 | PPC16 |
| PG 21 | 13,0-18,0 | 0.512-0.709 | 11 | 0.433 | 28,3 | 1.114 | 33 | 1.299 | 33 | 1.299 | 38,0 | 1.496 | 37,0 | 1.457 | PPC21 |
| PG 29 | 18,0-25,0 | 0.709-0.984 | 11 | 0.433 | 37,0 | 1.457 | 42 | 1.654 | 42 | 1.654 | 47,3 | 1.862 | 41,0 | 1.614 | PPC29 |

B. Packaging Requirements

- 1) Standard Package 10 glands per package

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.