



# SPECIFICATIONS

1. CASE:  
18 GA. (.048) CRS, TIN PLATED
2. RATED CURRENT:  
60A
3. RATED VOLTAGE:  
250VAC, 50/60Hz
4. TEST VOLTAGE:  
LINE TO LINE: 1.7KVDC  
LINE TO GROUND: 2.2KVDC
5. LEAKAGE CURRENT:  
1.6mA @ 250VAC, 50Hz


REVISION			
LTR	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	08-15-02	LE
B	REVISED MARKING	03-06-03	LE



INSERTION LOSS (50Ω TYPICAL)

	.05 MHz	.15 MHz	.50 MHz	1.5 MHz	5.0 MHz	20 MHz
L/L	20 db	45 db	60 db	52 db	48 db	60 db
L/G	2 db	45 db	60 db	58 db	58 db	60 db

## SCHEMATIC



NEXT ASSY	USED ON
APPLICATION	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± .XX ±.030 ± .XXX ±.010	CONTRACT NO.	
	APPROVALS	DATE
MATERIAL	DRAWN	DATE
	CHECKED	DATE
FINISH		

**FILTER CONCEPTS INC.**

**APPLICATION DRAWING**

**SF60 F FILTER**

SIZE	CODE IDENT NO.	DRAWING NO.
<b>B</b>		<b>7491</b>
SCALE	3/5	SHEET 1 OF 1