

SMP-J-B-GF-ST-1450



SMP-PF-P-HH-ST-EM3



SMP-J-C-GF-RA-CA7



SMP-PF-P-GF-ST-TH2



SMP-J-C-GF-ST-CS5



SMP-J-B-GF-ST-0645

SMP SERIES

50 Ω SMP JACKS/PLUGS & ADAPTOR

SMP-PF, SMP-PL, SMP-PS, SMP-PC
Mate with:
SMP-B Bullet Adaptor

Cable Mates:
RF405, RF25S

SPECIFICATIONS

For complete specifications see
www.samtec.com?SMP-TH,
www.samtec.com?SMP-EM,
www.samtec.com?SMP-B or
www.samtec.com?SMP-CA

Shell Material:
Au plated Brass (-TH2, -EM3)
Au plated BeCu (-J-B, -J-C)

Contact Material:
Brass (-TH2, -EM3)
BeCu (-CA)

Insulator Material:
PTFE

Impedance:
50 Ω

Frequency Range:
DC to 40 GHz,
DC to 20 GHz (25 AWG)

Working Voltage:
335 Vrms min

Dielectric Withstanding:
500 Vrms min

Engagement Force:
-PF: 15 lbs. max
-PL: 10 lbs. max
-PS & -PC: 2 lbs. max

Disengagement Force:
-PF: 2 lbs. min
-PL: 2 lbs. min
-PS & -PC: 0.5 lbs. min

Operating Temperature:
-65 °C to +165 °C

RoHS Compliant:
Yes

PROCESSING

Lead-Free Solderable:
Yes

ALTERNATIVE SOLUTIONS

The SMP Series is an alternative to the Corning Gilbert GPO Series. The SMPM Series is in development.

Note:
While optimized for 50 Ω applications, this connector can also perform well in certain 75 Ω applications. Contact RFGGroup@samtec.com for further information.

SMP	GENDER	TYPE	PLATING	ORIENTATION	TERMINATION										
		-P = PCB Mount	-GF = 10 μ" (0.25 μm) Gold center contact, Gold Flash outer contact (-TH2 only)	-ST = Straight	-TH2 = Through-hole										
		-PF = Plug, Full Detent	-HH = 30 μ" (0.76 μm) Gold center and outer contact (-EM3)	<table border="1"> <thead> <tr> <th>GENDER</th> <th>A DIA</th> </tr> </thead> <tbody> <tr> <td>-PF</td> <td>(4.19) .165</td> </tr> <tr> <td>-PL</td> <td>(5.99) .236</td> </tr> <tr> <td>-PS</td> <td></td> </tr> <tr> <td>-PC</td> <td></td> </tr> </tbody> </table>	GENDER	A DIA	-PF	(4.19) .165	-PL	(5.99) .236	-PS		-PC		-EM3 = Drop-in Edge Mount (Not available with -PC)
GENDER	A DIA														
-PF	(4.19) .165														
-PL	(5.99) .236														
-PS															
-PC															
		-PL = Plug, Limited Detent													
		-PS = Plug, Smooth Bore													
		-PC = Plug, Catcher's Mitt													

-PF/-PL/-PS-TH2

-PC-TH2

-EM3

EXTRACTION TOOL

- CAT-EX-SMP-01 Contact Samtec

APPLICATION

LENGTH	BOARD SPACE
-0645	(9.05) .356
-1450	(17.10) .673

SMP	J	TYPE	PLATING	ORIENTATION	BULLET LENGTH	CABLE END
		-B = Bullet Adaptor	-GF = 10 μ" (0.25 μm) Gold center contact, Gold Flash outer contact	-ST = Straight	Leave blank for cable end	Leave blank for bullet type
		-C = Cable End	-RA = Right-angle (Not available with -B)		-0645 = 6.45 mm (.254")	-CA7 = RG 405 (.086" DIA) Semi-flexible Cable
					-1450 = 14.50 mm (.571")	-CS5 = MWC-2550-01 25 AWG Microwave Cable

-0645

-1450

-ST-CXX

-RA-CXX

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.