

FOC-TO-6LCD-OM2-IP66 - 1422711

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Distributor box for wall mounting, ready to splice, 1x cassette, 2x comb for shrink splice protection, 12x shrink splice protection, 12x fiber pigtail, for 7x M20 screw connections, 1x incoming, with built-in outgoing 6x M20 screw connections

Your advantages

- ✓ fully prepared ready to splice
- ✓ including shrink splice protection

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 313924
GTIN	4055626313924

Technical data

Mechanical characteristics

Number of slots	12
Fiber type	GOF
Color	light grey RAL 7035
Degree of protection	IP66
No. of cable outlets	7

Ambient conditions

Ambient temperature (operation)	-20 °C ... 40 °C
Degree of protection	IP66

Material data

Flammability rating according to UL 94	HB
Housing material	Polystyrene
Cable gland material	PA
Height	90 mm

Standards and Regulations

Flammability rating according to UL 94	HB
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
------------	---

FOC-TO-6LCD-OM2-IP66 - 1422711

Technical data

Environmental Product Compliance

	No hazardous substances above threshold values
--	--

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>