9001SK43J38LRFR



Main

Range of product	Harmony 9001SK
Product or component type	Selector switch
Device short name	9001SK
Type of operator	Maintained
Operator profile	Gloved hand knob red

Complementary

Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Product weight	0.13 lb(US) (0.059 kg)	
Shape of signaling unit head	Round	
Operator position information	3 positions	
Contacts type and composition	Without contact block	_
Mechanical durability	500000 cycles	
Light block supply	Direct	
Light source	LED	
Bulb base	BA 9s	
Light block colour	Red	
[Us] rated supply voltage	120 V AC/DC	
Compatibility code	9001SK	

Environment

Environment		
protective treatment	TC	
ambient air temperature for storage	-40158 °F (-4070 °C)	
ambient air temperature for operation	-13158 °F (-2570 °C)	
electrical shock protection class	Class II conforming to IEC 61140	
IP degree of protection	IP66 conforming to IEC 60529	_
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 4 NEMA 6	
standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 CSA C22.2 No 14	
product certifications	NEMA UL 508	
vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
shock resistance	50 gn conforming to IEC 60068-2-27	

Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov
Contractual warranty	
Warranty period	18 months

