

Main

Device short name	L100
Series name	Severe duty

Complementary

Line Rated Current	20 A
AWG gauge	AWG 12 1 AWG 14 2
Body material	Cast aluminium
Contact code designation	A600 P600
Contact operation	Double-break isolated
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Function available	Two circuit - single operation
Material	Plastic front cover
Mounting support	Panel
Switch function	2-pole switch
Torque value	190 ozf.in
Connector type	Male 4 pins

Environment

ambient air temperature for operation	0...200 °F
NEMA degree of protection	NEMA 1/4/13
product certifications	CE CSA LR25490 class 3211 03 UL listed file E42259 CKN NKCR
vibration resistance	30 gn 10...55 Hz

Offer Sustainability

Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------