PHŒNIX CONTACT

SMSTB 2,5/ 5-STF-5,08 GY35AUBD - 1707570

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB connector, nominal current: 12 A, number of positions: 5, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, color: light gray, contact surface: Gold

The figure shows a 10-position version of the product

Your advantages

☑ Gold-plated contacts ensure transfer quality remains stable over the long term

☑ Well-known connection principle allows worldwide use

☑ Optimized for tight installation situations: operation and conductor connection from one direction

☑ Screwable flange for superior mechanical stability

☑ Low temperature rise, thanks to maximum contact force

☑ Allows connection of two conductors

Key Commercial Data

Packing unit	50 pc
Minimum order quantity	1000 pc
GTIN	4 046356 933391
GTIN	4046356933391

Technical data

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

PHŒNIX CONTACT

SMSTB 2,5/ 5-STF-5,08 GY35AUBD - 1707570

Approvals

Approvals

CSA / EAC / cULus Recognized

Ex Approvals

Approval details

CSA		http://www.csagroup.org/services-industries/product-listing/	13631
		D	B
Nominal voltage UN		300 V	300 V
Nominal current IN		10 A	15 A
mm²/AWG/kcmil		28-12	28-12

EAC			B.01742

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19931011
		D	B
Nominal voltage UN		300 V	300 V
Nominal current IN		10 A	15 A
mm²/AWG/kcmil		30-12	30-12