

## Coaxial Cable Connector 16\_MCX-50-3-8/111\_N

### Description

Right angle cable plug

Interface standards

IEC 60169-36\_CECC 22220

### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 6 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact soldered  
Weight 0.0009 kg

#### Environmental Data

Operating temperature -55 °C to 155 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

### Related Documents

Outline drawing DOU-00007971  
Assembly instruction DOC-0000181872

### Ordering Information

Bulk 100 pcs package 16\_MCX-50-3-8/111\_NH

### Additional Information

Suitable cables EZ\_141\_TP\_M17, MULTIFLEX\_141, SUCOFORM\_141

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[16\\_MCX-50-3-8/111\\_NH](#)