

# MIL-F-19207 military qualified panel-mount fuse holders

Military specification	Government designation	* Bussmann™ series commercial equivalent	Electrical ratings	Fuse family accommodated	Knob Type	Number of poles	Max. panel thickness
MIL-F-19207/1	FHL10U	HGA-C				2	
MIL-F-19207/1	FHL10G	—		F02, F03	Clear, neon, F-S		
MIL-F-19207/2	FHL11U	HGB-C	30 A, 90-250 V				1/8"
MIL-F-19207/2	FHL11G	—					
MIL-F-19207/3	FHL12U	HGC Series		F60, F07, F09	Clear, neon, Oct.		
MIL-F-19207/3	FHL12G	—					
MIL-F-19207/8	FHL17G1	HKL	20 A, 90-250 V				
MIL-F-19207/9	FHL18G1-1		20 A, 12-22 V				
MIL-F-19207/9	FHL18G1-2		20 A, 23-33 V				
MIL-F-19207/9	FHL18G1-3		20 A, 34-45 V				
MIL-F-19207/9	FHL18G1-4		20 A, 46-60 V	F02, F03	Amber, incandescent, F-S	1	
MIL-F-19207/9	FHL18G1-5	HXX	20 A, 61-80 V				
MIL-F-19207/9	FHL18G1-6		20 A, 81-90 V				
MIL-F-19207/9	FHL18G1-7		20 A, 2.5-4 V				1/16"
MIL-F-19207/9	FHL18G1-8		20 A, 5-7 V				
MIL-F-19207/9	FHL18G1-9		20 A, 8-12 V				
MIL-F-19207/10	FHN19G†	HCM	15 A, 250 V	F05, F06	Bayonet		
MIL-F-19207/11	FHN20G	HTA	20 A, 250 V	F02, F03			
MIL-F-19207/12	FHL22W†	HPF-C	15 A, 250 V	F10	Clear		
MIL-F-19207/13	FHN23W†	HPC-D	30 A, 500 V	F60, F09	Screw		
MIL-F-19207/16	FHN26G1	HKP	30 A, 250 V		Bayonet		
MIL-F-19207/18	FHL29G-1		30 A, 12-22 V				
MIL-F-19207/18	FHL29G-2		30 A, 23-33 V				
MIL-F-19207/18	FHL29G-3	HGN-CI	30 A, 34-45 V			2	
MIL-F-19207/18	FHL29G-4		30 A, 46-60 V				
MIL-F-19207/18	FHL29G-5		30 A, 61-80 V				
MIL-F-19207/18	FHL29G-6		30 A, 81-90 V	F02, F03	Amber, incandescent, F-S		1/8"
MIL-F-19207/19	FHL30G-1		30 A, 12-22 V				
MIL-F-19207/19	FHL30G-2		30 A, 23-33 V				
MIL-F-19207/19	FHL30G-3	HGF-C	30 A, 34-45 V				
MIL-F-19207/19	FHL30G-4		30 A, 46-60 V				
MIL-F-19207/19	FHL30G-5		30 A, 61-80 V			1	
MIL-F-19207/19	FHL30G-6		30 A, 81-90 V				
MIL-F-19207/20	FHN31G1†	HJM	5 A, 250 V	F01	Bayonet		1/16"
MIL-F-19207/26	FHN42W	HWA-AF	5 A, 125 V	FM01	—		
MIL-F-19207/36	FHN55W	HKP/RFI	30 A, 250 V	F02, F03	RFI Shield		1/8"
MIL-F-19207/38	FHL57G	—	15 A, 125 V	F77A	Clear, neon, F-S	2	

**Designation/description**

FHL = Indicating holder  
 FHN = Non-indicating holder  
 F-S = Flat-sided knob  
 G = Drip proof  
 Oct. = Octagonal knob  
 U = Unsealed  
 W = Waterproof

\* Commercial equivalent part number is for basic design reference only, NOT intended to be used as a substitute for the military part number.

† These government designations are obsolete. Their appearance in this table is for historical reference only.



Powering Business Worldwide

The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
Eaton.com

Bussmann Division  
114 Old State Road  
Ellisville, MO 63021  
United States  
Eaton.com/bussmannseries

© 2018 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 1214 — BU-SB08838  
September 2018

Eaton and Bussmann are valuable trademarks of Eaton in the US and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

For Eaton's Bussmann series  
product information,  
call **1-855-287-7626** or visit:  
**Eaton.com/bussmannseries**

Follow us on social media to get the  
latest product and support information.

