



| JKL LAMP NUMBER | VOLTS RATED | AMPS ±10% | MSCP ±25% | LUMENS ±25% | AVERAGE LIFE HRS. | FILAMENT TYPE |
|-----------------|-------------|-----------|-----------|-------------|-------------------|---------------|
| 1728 | 1.4 | .060 | .010 | 0.13 | 3,000 | C-2R |
| 2169 | 2.5 | .350 | .200 | 2.51 | 20,000 | C-2R |
| 2140 | 2.5 | .350 | LENS END | | 20,000 | C-2R |
| 1738 | 2.7 | .060 | .040 | 0.50 | 6,000 | C-2R |
| 2200 | 5.0 | .060 | .050 | 0.63 | 100,000 | C-2R |
| 3151 | 5.0 | .060 | .150 | 1.89 | 5,000 | C-2R |
| 2203 | 5.0 | .115 | .150 | 1.89 | 40,000 | C-2R |
| 1730 | 6.0 | .040 | .030 | 0.38 | 10,000 | C-2V |
| 1784 | 6.0 | .200 | .630 | 7.92 | 1,000 | C-2R |
| 2180 | 6.3 | .040 | .030 | 0.38 | 20,000 | C-2F |
| 1739 | 6.3 | .075 | .230 | 2.89 | 1,000 | C-2R |
| 8350 | 6.3 | .150 | .450 | 5.66 | 3,000 | C-2R |
| 2181 | 6.3 | .200 | .400 | 5.03 | 50,000 | C-2F |
| 2112 | 6.3 | .200 | .550 | 6.91 | 5,000 | C-2R |
| 2178 | 8.0 | .085 | .150 | 1.89 | 25,000 | C-2V |
| 1869 | 10.0 | .014 | .004 | 0.05 | 50,000 | C-2F |
| 2107 | 10.0 | .040 | .080 | 1.01 | 30,000 | C-2F |
| 2174 | 12.0 | .040 | .120 | 1.51 | 10,000 | C-2F |
| 2182 | 14.0 | .080 | .300 | 3.77 | 50,000 | C-2F |
| 1705 | 14.0 | .080 | .500 | 6.29 | 2,500 | C-2F |
| 2162 | 14.0 | .100 | .500 | 6.29 | 50,000 | C-2F |
| 2102 | 18.0 | .040 | .150 | 1.89 | 10,000 | C-2F |
| 2176 | 24.0 | .050 | .500 | 6.29 | 2,000 | C-2F |
| 2185 | 28.0 | .040 | .200 | 2.51 | 50,000 | C-2F |
| 2187 | 28.0 | .040 | .300 | 3.77 | 25,000 | C-2F |
| 1764 | 28.0 | .040 | .340 | 4.27 | 4,000 | C-2F |
| 1749 | 28.0 | .060 | .340 | 4.27 | 25,000 | C-2F |
| 8361 | 28.0 | .065 | .650 | 8.17 | 5,000 | C-2F |
| 1918 | 32.0 | .040 | .340 | 4.27 | 20,000 | C-2F |
| FW48 | 48.0 | .020 | .120 | 1.51 | 5,000 | C-2F |

- NOTES:
 1. GLASS ENVELOPE TO BE TIPLESS AND SEAMLESS.
 2. LEAD WIRES TO BE TINNED DUMET.

| | | | | | | | |
|----------|--|------------|--|--|--|--|--|
| F | DELETE CANCELLED PART # 1783 PER COMP LIST 6/24/07 | 7/22/05 | METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0 | JKL COMPONENTS CORPORATION TITLE T-1 3/4 STANDARD WIRE TERMINAL LAMP MULTI LISTING | | | |
| E | LEAD LENGTH 38.1 MIN. TO 25.4 MIN. | 02/07/00 | | | | | |
| D | DRAW CONVERTED TO CAD-LEAD LENGTH 1.00 TO 38.1MIN.-DELETED 2158, 2129, FW23, FW90, 8805, 8946, 8425, FW28, FW36, FW60-DIM'S TO METRIC ONLY | 01/01/00 | THIRD ANGLE PROJECTION | SIZE A FSCM NO. 55335 DRAWING NO. WIRE TERMINAL T-1 3/4 | | | |
| C | ADD FILAMENT TYPE | 3/23/98 | | | | | |
| B | CHNG MSCP & LUMENS ON FW48 | 4/1/98 | DRAWN BY L. WENGSTROM APPVD BY J.K. DATE 7/22/05 | SCALE NONE RELEASED DATE 8/15/88 REVISION DATE 7/22/05 REV. NO. F SHEET 1 OF 1 | | | |
| A | CHNG WIRE DIA & ADD NOTES | 3/27/96 | | | | | |
| | RELEASED | 8/15/88 | | | | | |
| REV. NO. | DESCRIPTION/ECO NUMBER | APPVD DATE | | | | | |