



Main

|                           |                                           |
|---------------------------|-------------------------------------------|
| Range of product          | Harmony 9001SK                            |
| Product or component type | Non-illuminated mushroom head push-button |
| Device short name         | 9001SK                                    |
| Bezel material            | Black plastic                             |

Complementary

|                              |                                                                        |
|------------------------------|------------------------------------------------------------------------|
| Mounting diameter            | 1.18 in (30 mm)                                                        |
| CAD overall width            | 1.81 in (46 mm)                                                        |
| CAD overall height           | 1.77 in (45 mm)                                                        |
| CAD overall depth            | 2.72 in (69 mm)                                                        |
| Product weight               | 0.21 lb(US) (0.095 kg)                                                 |
| Operating position           | Any position                                                           |
| Shape of signaling unit head | Round                                                                  |
| Type of operator             | Spring return                                                          |
| Operator profile             | Mushroom Ø 30 mm, cap/operator or lens colour:white (unmarked marking) |
| Mechanical durability        | 5000000 cycles                                                         |

Environment

|                                       |                                                                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| protective treatment                  | TC                                                                                                                               |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                                       |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                                       |
| electrical shock protection class     | Class II conforming to IEC 61140                                                                                                 |
| IP degree of protection               | IP66 conforming to IEC 60529                                                                                                     |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X                                                 |
| standards                             | EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>JIS C 852<br>UL 508<br>CSA C22.2 No 14<br>RoHS compliant |
| product certifications                | NEMA<br>UL 508<br>CSA LR25490 class 3211 03<br>UL listed file E78403 CCN NKCR                                                    |
| vibration resistance                  | 7 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                                                 |
| shock resistance                      | 50 gn conforming to IEC 60068-2-27                                                                                               |

Offer Sustainability

|              |              |
|--------------|--------------|
| 785901713739 | 785901713739 |
|--------------|--------------|

|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Compliant - since 0921 - Schneider Electric declaration of conformity                                                            | Compliant - since 0921 - Schneider Electric declaration of conformity                                                            |
| Reference not containing SVHC above the threshold                                                                                | Reference not containing SVHC above the threshold                                                                                |
| WARNING: This product can expose you to chemicals including:                                                                     | WARNING: This product can expose you to chemicals including:                                                                     |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|