

Relay connectors - ST-REL3-KG230/21/SO46 - 2832027

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in relay interface for protection against interference on the control side, with soldered-in miniature switching relay, contacts (AgNi): Medium to large loads, 1 PDT, 230 V AC input voltage

Your advantages

- ✓ Use of AC output cards, resulting in residual AC currents
- ✓ Resistant to interference currents
- ✓ High relay release voltage
- ✓ Applications with long control lines

RoHS

Key Commercial Data

Packing unit	10 pc
GTIN	 4 017918 078577
GTIN	4017918078577

Technical data

Dimensions

Width	20.8 mm
Height	42.5 mm
Depth	112 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Coil side

Nominal input voltage U_N	230 V AC
Input voltage range in reference to U_N	0.9 ... 1.1
Typical input current at U_N	18 mA AC
Typical response time	10 ms

Relay connectors - ST-REL3-KG230/21/SO46 - 2832027

Technical data

Coil side

Typical release time	8 ms
Protective circuit	Bridge rectifier Bridge rectifier
	Surge protection Varistor
	RC element RC element
Operating voltage display	Yellow LED
Power dissipation for nominal condition	4.14 W

Contact side

Contact type	Single contact, 1-PDT
Type of switch contact	Single contact
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Maximum inrush current	8 A
Limiting continuous current	6 A
Interrupting rating (ohmic load) max.	95 W (at 24 V DC)
	50 W (at 48 V DC)
	45 W (at 60 V DC)
	35 W (at 110 V DC)
	55 W (at 220 V DC)
	2000 VA (for 250 V AC)

General

Test voltage relay winding/relay contact	2.5 kV AC (50 Hz, 1 min.)
Mechanical service life	approx. 2×10^7 cycles
Mounting position	any

Standards and Regulations

Standards/regulations	IEC 60664
	EN 50178
Insulation	Basic insulation
Degree of pollution	2
Overvoltage category	III


Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Relay connectors - ST-REL3-KG230/21/SO46 - 2832027

Circuit diagram



Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC



RU C-
DE.A*30.B.01082

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>