

## LAURA-M-PG

~30° medium beam. Assembly with white holder and location pins.

### TECHNICAL SPECIFICATIONS:

Dimensions	21.6 mm
Height	13.1 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LAURA-M	Single lens	PMMA		
LAURA-HLD-PIN	Holder	PC		

### ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP12633_LAURA-M-PG	Single lens	1960	392	98	11.5
» Box size: 476 x 273 x 292 mm					







#### PHOTOMETRIC DATA (MEASURED):





LED XP-E-HEW  
FWHM 27.0°  
Efficiency 85 %  
Peak intensity 2.600 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED XP-G  
FWHM 32.0°  
Efficiency 91 %  
Peak intensity 2.600 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED XT-E  
FWHM 29.0°  
Efficiency 92 %  
Peak intensity 3.200 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED LUXEON A  
FWHM 30.0°  
Efficiency 93 %  
Peak intensity 2.700 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





### PHOTOMETRIC DATA (MEASURED):





LED LUXEON Rebel  
FWHM 27.0°  
Efficiency 88 %  
Peak intensity 2.900 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED NVSxx19A  
FWHM 28.0°  
Efficiency 91 %  
Peak intensity 3.000 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED OSLOM Square EC  
FWHM 28.0°  
Efficiency 90 %  
Peak intensity 2.700 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### PHOTOMETRIC DATA (SIMULATED):




LED XP-E  
FWHM 33.0°  
Efficiency 96 %  
Peak intensity 2.879 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




LED NCSxx19A  
FWHM 27.0°  
Efficiency 94 %  
Peak intensity 3.696 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED OSLOM SSL 150  
FWHM 33.0°  
Efficiency 96 %  
Peak intensity 3.245 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED OSLOM SSL 80  
FWHM 28.0°  
Efficiency 95 %  
Peak intensity 3.518 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)