



Main

Range	TeSys
Product or component type	Auxiliary contact
Device application	Connection
Contacts type and composition	1 NO + 1 NC

Complementary

Range compatibility	TeSys GS switch
Contact operation	Early-break
[Ith] conventional free air thermal current	16 A 40 °C
[Ie] rated operational current	100 A 200 A 400 A
Mechanical durability	5000000 cycles
Type of operating handle	External frontal External left side External right side

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: Cancer - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>	WARNING: Cancer - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.