




1		2		3		4		5		6		7		8	
ALTW DCC. DEPT. CONFIDENTIAL 2017.07.17 ISSUED				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				B		LEN1770147		2017/07/11		Vicky		Update Note			
With Liquid Glue 點 防 水 膠  ⑦ Sealing Nut ⑥ Clamp Ring ⑤ Seals B2 ④ Seals B1 ③ Lock Nut ② Connector ① O-Ring															
ALTW CONFIDENTIAL 2017-07-11 R&D DEPT.   Pin Assignments Front View 前視圖 Note: * Important Dimension * Waterproof Rate: IP66 * Ring: EPDM, Black * Housing: Nylon+GF, Black * Male Pin: Copper Alloy, Gold Plated * Lock Nut: Nylon+GF, Black * Seals: EPDM, Black * Clamping Ring: Nylon+GF, Black * Sealing Nut: Nylon+GF, Black * PE Bag: 90mm*85mm * Liquid Glue: Clear * Seals B1 for Cable OD: Ø4.5mm~Ø6.5mm (防水墊圈B1線徑: Ø4.5mm~Ø6.5mm) * Seals B2 for Cable OD: Ø3.5mm~Ø5.3mm (防水墊圈B2線徑: Ø3.5mm~Ø5.3mm) * One Set Unassembled in One PE Bag (每一組未組裝, 放置於一個PE袋, 並封口)															
UNIT:mm		 		TITLE Standard, Assy Lock 3Pin F Conn M Pin				ITEM NO BD-03BFMA-LL6001				DRAWN BY Vicky		DATE 2017-07-11	
TOLERANCE .X ±0.25 .XX ±0.1 .XXX ±0.05 ANGLES ±1°		SCALE 1:1		SIZE A4		SHEET 1 OF 1		DWG NO BD-03BFMA-LL6001				CHECKED BY Rita		DATE 2017-07-11	
		REV. B		WC-REV. A.2		 : Inspection item		CUSTOMER ALTW				APPROVED BY Max		DATE 2017-07-11	
		2		3		4		5		6		7		8 FMW10702-01-02A1	