




REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
H6		REVISED PER ECO-11-018497	09SEP2011	DLD	DCM
H7		REVISED PER ECO-14-015177	15OCT2014	DLD	DCM
H8		REVISED PER ECO-15-011500	07AUG2015	DLD	DCM

△ MATERIAL:
HARNESS - 35% GLASS FILLED PA66, BLACK
ALT MAT'L - 30% GLASS FILLED sPS, BLACK

SPACER - 40% GLASS FILLED PPS, RED
ALT MAT'L - 30% GLASS FILLED sPS, RED

COVER - 35% GLASS FILLED PA66, BLACK
ALT MAT'L - 30% GLASS FILLED LCP, BLACK

CAM LEVER - 35% GLASS FILLED NYLON, GRAY
GROMMET - SILICONE, BROWN
PERIMETER SEAL - SILICONE, GREEN

2. CAM LEVER AND SPACER ARE SHIPPED IN PRE-LATCH POSITION.

△ 3 SEE PINOUT CHART FOR CLOSED CIRCUIT CONFIGURATIONS.

△ 4 CAVITIES WITH A NUMERIC SYMBOL INDICATES CLOSED TERMINAL LOCATIONS.
BLANK CAVITIES INDICATE OPEN TERMINAL HOLE LOCATIONS.

CHART FOR CLOSED CIRCUIT CONFIGURATIONS SHEET 2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. VESTAL 15OCT2003	TE Connectivity	
		CHK D. STRAUSSER 15OCT2003		
DIMENSIONS:		APVD D. STRAUSSER 15OCT2003	NAME	
mm		PRODUCT SPEC	PCM	
		APPLICATION SPEC	HARNESS ASSEMBLY, 30-WAY CONNECTOR	
		WEIGHT	SIZE A1	RESTRICTED TO
MATERIAL		CUSTOMER DRAWING	CAGE CODE 00779	DRAWING NO. 1438083
			SCALE 3:1	SHEET 1 OF 2
				REV H8

