

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	06SEP2018	YC	CW

M4 SCREW
RECOMMENDED TIGHTENING TORQUE 1.2N.m
M4螺丝, 推荐锁紧力矩 1.2N.m

4X M3 SCREW
RECOMMENDED TIGHTENING TORQUE 0.5N.m
4X M3螺丝, 推荐锁紧力矩 0.5N.m

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250 V
RATED CURRENT: 10 A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 4 KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.14-2.5 mm² (26-14 AWG)
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.

注释:

- 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 4 KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: 0.14-2.5 mm² (26-14 AWG)
接线类型: 冷压接
- 端子需要单独订购.

PANEL CUT OUT FOR INSERTS FOR USE
WITHOUT HOODS/HOUSINGS
不使用防护外壳芯件的面板开孔安装尺寸

T2020802201-100	HD-040-FJ 41-80	HD-040 FEMALE INSERT, STAMPING 41-80 HD-040母插, 卷皮针 41-80
-----------------	--------------------	---

PART NUMBER
料号

PART DESCRIPTION
描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 06SEP2018

YORK CHEN

CHK 06SEP2018

GINO YAO

APVD 06SEP2018

CHRIS WANG

PRODUCT SPEC

108-137042

APPLICATION SPEC

114-137042

WEIGHT

-

CUSTOMER DRAWING

TE Connectivity

NAME

HD-040-FJ 41-80

SIZE

A3

CAGE CODE

-

DRAWING NO

T2020802201100

RESTRICTED TO

-

SCALE

1:1

SHEET

OF

1

REV

A

1470-19 (3/13)