




REVISIONS				
P	LTR	DESCRIPTION	DATE	APVD
A		NEW RELEASE PER ECO-14-013325	09-01-14	DM DM



1. THIS PART IS USED ON
HD10-3-XXX RECEPTALCES
HD14-3-XXX RECEPTACLES
WHERE XXX IS PIN ARRANGEMENTS. SEE INVIDUAL CUSTOMER DRAWINGS
2. MATERIAL: LANYARD-GALVANIZED STEEL WITH NYLON COATING, DUST CAP-PA66
3. TEMPERATURE RATING: -55°C TO +125°C [-67°F TO +257°F]
4. PART NO. HDC16-3-LA

2014

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

© COPYRIGHT 2014 BY TE CONNECTIVITY

THIS DRAWING IS UNPUBLISHED.

DIMENSIONS: MM [INCH]	DWN D. MEYER 01SEP2014	MATERIAL SEE NOTE 2	FINISH GRAY
	CHK I. GRANTCHAROVA 01SEP2014		
TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD D. MEYER 01SEP2014		
0 PLC ±	PRODUCT SPEC	SIZE A 4	CAGE CODE 4AFU8
1 PLC ±	APPLICATION SPEC	DRAWING NO	RESTRICTED TO
2 PLC ± 0.63 [0.025]		SCALE NONE	SHEET 1 OF 1
3 PLC ±	WEIGHT 8.18g	C = HDC16-3-LA	
4 PLC ±	Customer Drawing		
ANGLES ± 5°			

