Product datasheet **Characteristics**

ZB4BA222





Main

inani	
Range of product	Harmony XB4
Product or component type	Head for non-illuminated push-button
Device short name	ZB4
Mounting diameter	0.87 in (22 mm)
Sale per indivisible quantity	1
Head type	Standard
Shape of signaling unit head	Round
Operator profile	Flush RESET

Complementary

Mechanical durability	y 10000000 cycles
meenamear uurabiiit	

Environment

ТН
-40158 °F (-4070 °C)
-40158 °F (-4070 °C)
Class I conforming to IEC 60536
IP67 IP66 conforming to IEC 60529 IP69K IP69
NEMA 13 NEMA 4X
IK06 conforming to IEC 50102
EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14
BV CSA DNV GL LROS (Lloyds register of shipping) RINA UL listed
5 gn (f = 2500 Hz) conforming to IEC 60068-2-6
30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0627 - Schneider Electric declaration of conformity	Compliant - since 0627 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:



Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period

18 months

