

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT – By –

ALL RIGHTS RESERVED.

LOC

H

DIST

—

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	12NOV2013	GSK	BvH
	A1	ECR–14–011671	14AUG2014	GSK	BvH

NOTES:

Tolerances cable lengths:

0m to 0.5m	+30mm
0.5m to 1.0m	+50mm
1.0m to 3.0m	+100mm
< 3.0m	+1.5%

VIEW 'A'

A

L

20mm

PVC CABLE

No./diameter of wires	4 x 0.25 mm ²
Wire isolation	PVC (br, wh, bl, bk)
C–track properties	
Jacket	PVC (UL/CSA)
Outer diameter	approx. 4.8 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	–30...+80 °C
Temperature range (mobile)	–5...+80 °C

TECHNICAL DATA

Operating voltage	max. 30 V AC/DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread M8 x 1 mm (recommended torque 0.4 Nm) self–securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)

PUR CABLE

No./diameter of wires	4 x 0.25 mm ²
Wire isolation	PP (br, wh, bl, bk)
C–track properties	5 million
Jacket	PUR (UL/CSA)
Outer diameter	approx. 4.4 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	–40...+80 °C
Temperature range (mobile)	–25...+80 °C

4 pos

10mtr

5mtr

3mtr

1.5mtr

PVC

Black

1–2273011–4

4x22AWG PVC 10.0m

8

4 pos

10mtr

5mtr

3mtr

1.5mtr

PUR

Black

2273011–4

4x22AWG PUR 10.0m

4

LENGTH”L”

MATERIAL

JACKET COLOR

TE PN

DESCRIPTION

ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± –
1 PLC	± –
2 PLC	± –
3 PLC	± –
4 PLC	± –
ANGLES	± –
FINISH	–

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

SATHISH KUMAR .G

CHK

B.VELDHoven

APVD

A.VAN ZANDVOORT

PRODUCT SPEC

108–19483

APPLICATION SPEC

114–32127

WEIGHT

–

CUSTOMER DRAWING

12NOV2013

12NOV2013

12NOV2013

NAME

M8 X 1.0 ANGLED SOCKET PIGTAIL

–

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=2273011

–

STE

TE Connectivity

SCALE

NTS

SHEET

1 OF 1

REV

A1

1470–19 (3/11)