


f	6	6	6	6	6	6	6	6	6		6	6	6	6	6	6	6	6	6
e	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
d	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
c	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
b	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
a	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
z	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	0	0
P	0	0				1				1				2					
O	1	5				0				5				0					
S																			

Technical drawing of a mechanical part with the following dimensions and notes:

- Overall width: 15.40 ± 0.50
- Inner width: 11.70 ± 0.10
- Vertical dimension (left): $+0.15$ and $13.45 - 0.10$
- Vertical dimension (bottom): $+0$ and $3.00 - 0.10$
- Notes:
 - NOTE 3 points to the inner width dimension.
 - NOTE points to the overall width dimension.



Technical drawing of a connector assembly. The drawing shows two views of a component, labeled 4 and 6, with dimensions and a seating plane indicated.

Dimensions:

- View 4: 8.20 (overall length), 3.70 (length of the rightmost section).
- View 6: 11.20 (overall length), 3.70 (length of the rightmost section).

Seating Plane for Connector: Indicated by a vertical line and an arrow pointing to the rightmost section of the component.

LEAD FREE INDICATOR : LF = LEAD FREE
(DIGIT 15 & 16)

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS. A , 201572 , 001

CATALOG NO: HM2P66PD5115----

[illegible]