


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [0764101134](#)  
**Status:** **Active**  
**Overview:** [Impact™ Backplane Connector and Cable Assembly System](#)  
**Description:** Impact™ 100 Ohm 3 Pair Right Angle Male Header, Unguided, Right Endwall, 10 Columns, 90 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.46mm, Lead-Free

**Documents:**  
[3D Model](#)  
[Drawing \(PDF\)](#)  
[Product Specification PS-76060-999 \(PDF\)](#)  
[Application Specification AS-76060-990 \(PDF\)](#)  
[Application Specification AS-76060-9999 \(PDF\)](#)  
[Packaging Specification PK-70873-762 \(PDF\)](#)  
[RoHS Certificate of Compliance \(PDF\)](#)

|                                |                                                                       |
|--------------------------------|-----------------------------------------------------------------------|
| <b>Agency Certification</b>    |                                                                       |
| UL                             | E29179                                                                |
| <b>General</b>                 |                                                                       |
| Product Family                 | Backplane Connectors                                                  |
| Series                         | <a href="#">76410</a>                                                 |
| Application                    | Coplanar                                                              |
| Application Tooling Documents  | TM-622018799                                                          |
| Component Type                 | PCB Header                                                            |
| Overview                       | <a href="#">Impact™ Backplane Connector and Cable Assembly System</a> |
| Product Name                   | Impact™                                                               |
| UPC                            | 884982004139                                                          |
| <b>Physical</b>                |                                                                       |
| Circuits (Loaded)              | 90                                                                    |
| Circuits (maximum)             | 90                                                                    |
| Color - Resin                  | Black                                                                 |
| Durability (mating cycles max) | 200                                                                   |
| First Mate / Last Break        | No                                                                    |
| Flammability                   | 94V-0                                                                 |
| Guide to Mating Part           | No                                                                    |
| Keying to Mating Part          | Yes                                                                   |
| Material - Metal               | High Performance Alloy (HPA)                                          |
| Material - Plating Mating      | Gold                                                                  |
| Material - Plating Termination | Tin                                                                   |
| Material - Resin               | High Temperature Thermoplastic                                        |
| Net Weight                     | 7.940/g                                                               |
| Number of Columns              | 10                                                                    |
| Number of Pairs                | 3                                                                     |
| Number of Rows                 | 9                                                                     |
| Orientation                    | Right Angle                                                           |
| PC Tail Length                 | 1.20mm                                                                |
| PCB Locator                    | No                                                                    |
| PCB Retention                  | None                                                                  |
| PCB Thickness - Recommended    | 1.00mm                                                                |
| Packaging Type                 | Tray                                                                  |
| Pitch - Mating Interface       | 1.90mm                                                                |
| Pitch - Termination Interface  | 1.90mm                                                                |
| Plating min - Mating           | 0.762µm                                                               |
| Polarized to PCB               | No                                                                    |
| Stackable                      | No                                                                    |
| Temperature Range - Operating  | -55°C to +85°C                                                        |
| Termination Interface: Style   | Through Hole - Compliant Pin                                          |



Series image - Reference only

**EU ELV**  
**Not Relevant**

**EU RoHS**  
**Compliant**  
**REACH SVHC**  
Not Contained Per  
-ED/79/2015 (17  
December 2015)  
**Halogen-Free**  
**Status**  
**Low-Halogen**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS      Green Image  
ELV      Not Relevant

**Search Parts in this Series**  
[76410](#) Series

**Mates With**  
[76170](#) Impact™ 100 Ohm 3 Pair Right Angle Daughtercard

**Application Tooling | FAQ**  
*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*  
**Global**

| Description                                      | Product #                  |
|--------------------------------------------------|----------------------------|
| Daughter Card                                    | <a href="#">0622018646</a> |
| Module Installation                              |                            |
| Press-In Tool for 3-Pair by 10-Column Assemblies |                            |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.75A           |
| Data Rate                     | 25.0 Gbps       |
| Impedance                     | 100#            |
| Shield Type                   | N/A             |
| Shielded                      | No              |
| Voltage - Maximum             | 30V AC (RMS)/DC |

**Solder Process Data**

|                             |     |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|

**Material Info**

**Reference - Drawing Numbers**

|                           |                             |
|---------------------------|-----------------------------|
| Application Specification | AS-76060-990, AS-76060-9999 |
| Electrical Model Document | EE-76410-002                |
| Packaging Specification   | PK-70873-762                |
| Product Specification     | PS-76060-999                |
| S-Parameter Model         | SP-76410-002                |
| Sales Drawing             | SD-76410-001                |
| Symbol/Footprint Data     | SYM-76410-1134              |

Impact™ Right Angle0622024350  
Module Removal  
Tool (RAM)

This document was generated on 06/10/2016

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION